

PLANA

Indirect Trimless Linear

Plana features a 107mm wide slot with dual 12mm LED channels for high-output COB strips. Its trimless aluminum body embeds seamlessly into walls or ceilings, while the PC diffuser softens output into a clean gradient. End caps with or without wiring holes offer install flexibility. Ideal for continuous architectural lines with high CRI illumination.

SPECIFICATIONS

LED STRIP Fits LED strips up to 2 x 12mm (0.47 in)

 WATTAGE
 1.7W / 3.5W / 7.7W per

 LUMEN OUTPUT
 210 / 390 / 950 lm per

LENS Frosted

LENGTH OPTIONS Cut Points: 4 inch

CRI 90+


COLOR TEMPERATURE 27K / 3K / 35K / 4K

DIMMING Dimmable LED Drivers

CONNECTIONS End to End In-Field

RATING IP20
CERTIFICATIONS UL & ETL

Client:	
Order#:	
Project:	
Туре:	









ORDERING INFORMATION

PLANA	/	/	/ ,	/ ,	/	//	/
MODEL	LENGTH	LIGHT OUTPUT	COLOR TEMP	FINISH	LENS	VOLTAGE	DRIVER

MODEL	LENGTH	LIGHT OUTPUT	COLOR TEMP	FINISH	LENS	VOLTAGE	DRIVER
PLANA	79.2 79.2 in. XX Custom Length	1.7 W 1.7 Watts 3.5 W 3.5 Watts 7.7 W 7.7 Watts	27K 27OOK 30K 30OOK 35K 35OOK 40K 40OOK 50K 50OOK	WH White CC Custom Color	FL Frosted Lens	24 24 Volts	EB TRIAC ELV Dimming D10 0-10V Dimming HL2W Lutron 2-Wire HL3E Lutron ECO 3-Wire

Commerce CA 90040

DIMENSIONS

