

# **ARCUS**

## **Arc Linear**

ARCUS is a curved aluminum LED linear profile designed for wall-to-ceiling transitions. Its tool-free installation requires no slotting, making it easy to mount. ARCUS delivers soft, uniform, and anti-glare lighting with options for both upward and downward wall washing. A 23.2mm channel fits standard LED strips, while internal and external corner connectors ensure clean, continuous lines. With high CRI output and a flush PC diffuser, ARCUS offers sleek architectural illumination ideal for residential, hospitality, or commercial interiors.

#### **SPECIFICATIONS**

LED STRIP Fits LED strips up to 23.2mm (.91 in)

 WATTAGE
 1.7W / 3.5W / 7.7W

 LUMEN OUTPUT
 210 / 390 / 950 lm

 LENS
 Frosted Lens

LENGTH OPTIONS Cut Points: 4 / 1 / 1.3 inch

CRI 90+

COLOR TEMPERATURE 27K / 3K / 35K / 4K

DIMMING Dimmable LED Drivers

CONNECTIONS End to End In-Field

RATING IP20
CERTIFICATIONS UL & ETL

Client:	
Order#:	
Project:	
Туре:	









#### **ORDERING INFORMATION**

ARLA	/	/	/	/ ,	/ ,	/	<i>'</i>
MODEL	LENGTH	LIGHT OUTPUT	COLOR TEMP	FINISH	LENS	VOLTAGE	DRIVER

MODEL	LENGTH	LIGHT OUTPUT	COLOR TEMP	FINISH	LENS	VOLTAGE	DRIVER
ARLA	79.2 79.2 in.  XX Custom Length	1.7 W 1.7 Watts 3.5 W 3.5 Watts 7.7 W 7.7 Watts	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K	WH White CC Custom Color	<b>FL</b> Frosted Lens	<b>24</b> 24 Volts	EB TRIAC ELV Dimming D10 0-10V Dimming HL2W Lutron 2-Wire HL3E Lutron ECO 3-Wire

Commerce CA 90040

### **DIMENSIONS**

