

EXTORA

External Corner Linear

Designed for clean external corner lighting, EXTORA installs flush with drywall to form a crisp illuminated edge. Its angled profile softens output with a PC diffuser while blending into the wall finish via mud-in flanges. Pre-cut end caps and seamless splicing enable precise, uniform lines across architectural intersections.

Client: Order#: Project: Type:

	0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0	
Extora		







SPECIFICATIONS

LED STRIP Fits LED strips up to 10mm (.39 in)

 WATTAGE
 1.7W / 3.5W / 7.7W

 LUMEN OUTPUT
 210 / 390 / 950 lm

 LENS
 Frosted Lens

LENGTH OPTIONS Cut Points: 4 / 1 / 1.3 inch

CRI 90+

COLOR TEMPERATURE 27K / 3K / 35K / 4K

DIMMING Dimmable LED Drivers

CONNECTIONS End to End In-Field

RATING IP20
CERTIFICATIONS UL & ETL


ORDERING INFORMATION

EXTORA	/	/	/	/ ,	/ ,	/	<i>'</i>
MODEL	LENGTH	LIGHT OUTPUT	COLOR TEMP	FINISH	LENS	VOLTAGE	DRIVER

MODEL	LENGTH	LIGHT OUTPUT	COLOR TEMP	FINISH	LENS	VOLTAGE	DRIVER
EXTORA	79.2 79.2 in. XX Custom Length	1.7 W 1.7 Watts 3.5 W 3.5 Watts 7.7 W 7.7 Watts	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K	WH White CC Custom Color	FL Frosted Lens	24 24 Volts	EB TRIAC ELV Dimming D10 0-10V Dimming HL2W Lutron 2-Wire HL3E Lutron ECO 3-Wire

Commerce CA 90040

DIMENSIONS



2917 Vail Ave. Commerce CA 90040