

LUCERA

LED Linear Strip Luminaire

The Strip Light Series is a versatile fixture with an adjustable dip switch on the driver, letting you easily change wattage and color temperature for different project needs. Available in 4-foot and 8-foot sizes, it has a sleek architectural finish suited for modern spaces. The fixture includes secure lens-holding cables for safe installation and cleaning, and it can be customized with motion sensors or emergency battery backups. Built from powder-coated steel stamping, polycarbonate end cups, and high-transparency diffusers, it delivers both durability and refined style.

FEATURES

- Luminous part is integrated and fastened to fixture by snap locks.
- Changeable lighting module (R, M type for option).
- Tool-less accessed and easy to install.
- Field adjustable light output and CCT selectable.
- Bi-level motion sensor or battery backup are available



PERFORMANCE DATA

Product ID	Size	Wattage	Lumens	CCT	Efficacy	Angle
DLSL-GEN2-2MW30	2 FT	10, 15, 20, 25, 30W (Selectable)	1400, 2100, 2800, 3500, 4200	30K, 35K, 40K, 50K, 65K (Selectable)	135	110°
DLSL-GEN2-4MW45	4 FT	10, 20, 30, 38, 45W (Selectable)	1400, 2800, 4200, 5320, 6300			
DLSL-GEN2-8MW90	8 FT	20, 40, 60, 75, 90W (Selectable)	2800, 5600, 8400, 10500, 12600			
DLSL-GEN2-M2MW30	2 FT	10, 15, 20, 25, 30W (Selectable)	1400, 2100, 2800, 3500, 4200		140	130°
DLSL-GEN2-M4MW45	4 FT	5, 15, 25, 35, 45W (Selectable)	700, 2100, 3500, 4900, 6300			
DLSL-GEN2-M8MW90	8 FT	10, 30, 50, 70, 90W (Selectable)	1400, 4200, 7000, 9800, 12600			


ORDERING INFORMATION

DLSL / **GEN2** / **PROFILE** / **SIZE** / **WATTAGE** / **OPTIONS** / **WARRANTY**
SERIES PHASE

FIXTURE SERIES	
DLSL	Deco Linear Strip Luminaire
PHASE	
GEN2	Generation II: Multi Watt, Multi CCT
PROFILE	
-	Flat Lens
M	Mushroom
SIZE	
2	2 FT
4	4 FT
8	8 FT

WATTAGE	
MW30	10, 15, 20, 25, 30W (selectable)
MW45	10, 20, 30, 38, 45W (selectable)
MW90	20, 40, 60, 75, 90W (selectable)
OPTIONS	
-	None
MS	Motion Sensor
EM	Emergency Backup
MS-E	Motion Sensor and Emergency Driver
WARRANTY	
5	5 Year Warranty (included)
10	10 Year Warranty


Dimensions



	A	B	C
2'	24"	2.5"	3.1"
4'	48"	2.5"	3.1"
8'	96"	2.5"	3.1"

Photometric

POLAR GRAPH DACH-LED-36-35050-U-R



Maximum Candela = 1341.781 Located At Horizontal Angle = 0, Vertical Angle = 1
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cld.)

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD Effective Floor Cavity Reflectance 0.20

RC	60				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	177	177	177	177	113	113	113	113	106	106	106	100	100	100	94	94	94	92
1	105	95	94	89	101	96	91	87	90	86	83	85	80	79	80	77	75	72
2	95	85	78	71	91	83	76	70	78	72	67	73	66	64	69	65	62	59
3	86	75	66	59	83	72	64	58	68	61	55	64	58	54	61	56	52	49
4	78	66	57	50	75	64	55	49	60	53	47	57	52	46	54	48	44	42
5	72	59	49	42	69	57	48	42	54	46	41	51	44	39	48	43	38	36
6	66	53	44	37	64	51	43	36	49	41	35	46	40	34	44	38	33	31
7	62	48	39	32	60	47	38	32	44	37	31	42	36	30	40	34	30	28
8	57	44	35	29	55	42	34	29	40	33	28	39	32	27	37	31	27	25
9	54	40	32	26	52	39	31	26	37	30	25	36	29	25	34	28	24	22
10	50	37	29	23	48	36	28	23	34	28	23	33	27	22	32	26	22	20


*Hinge open design with toolless access. and open angle up to 110°.



LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Angle In Degrees	Angle In Degrees	Angle In Degrees
45	13964	7851	7168
55	12315	6298	5915
65	10372	5026	4895
75	7707	4015	4061
85	3550	3250	3410

Mounting Details



A:	End Cap
B:	Suspension-mount with v-hook
C:	Surface Mount
D:	T-Bar Clip Mounting hole
E:	Wiring Knockout

Accessories (Ordered and Shipped Separately)

Mounting

5011003-6	V-hook and Aircraft Cable Suspension Kit - 6'
5011003-10	V-hook and Aircraft Cable Suspension Kit - 10'

Sensor Options

External PIR sensor with 360 degree.



- Provide multi-level control based on motion and/or daylight contribution.
- Controls 0-10V VDC dimming LED drivers (or dimming ballasts).
- can also be used with non-dimming drivers.
- 40 degree range detector sensitivity.
- All control parameters are adjustable by using RC-100 remote(sold separately)



HD07VR-PH

Mounting Height
~12m/39.37ft Ceiling Mounted



Detection Distance
Radius 3-7m/9.84-22.96ft



HD07VR-P


Mounting Height
~6m/19.68ft Ceiling Mounted

Detection Distance
Radius 3-7m/9.84-22.96ft



Built-in PIR sensor with quick snap installation.

- Specially designed tiny PIR sensor.
- Easy remote control, daylight harvesting supported.
- 12VDC input, bi-level dimmable.



Mounting Height
~4m/13.12ft Ceiling Mounted

Detection Distance
Radius 2-4m/6.56-13.12ft

