




DOWP

LED Wall Pack Light

DOB-CCT Selectable
Wattage & CCT Selectable



3CCT Selectable
Photocell Switch



DOB Series

3CCT Selectable
3 Wattage Selectable




DOWP CCT Selectable 3 Wattage & 3 CCT Selectable

Features

Die-Casting aluminum housing with corrosion resistant polyester powder coat finish
Impact resistant UV stabilized polycarbonate lens
Built in daylight sensor with disable switch
UL, FCC, RoHS rated
Working temperature : -40°C to 50°C 0°C to 45°C (for built-in emergency series)
3-year warranty for DOB series

Dimensions

Wattage	L	W	H
20/24/28W	10.6"	6.6"	3.6"



Order Matrix

DOB Series

Model No.	Lumen (lm)	Efficacy (lm/w)	Voltage (V)	CCT Selectable
DOWP-GEN2-MW28	3360	120	120V	3000/4000/5000

C=AC120V DSN=With sensor without dimming

Wattage & CCT Selectable Serie

Model No.	Lumen (lm)	Efficacy (lm/w)	Voltage (V)	CCT Selectable
DOWP-GEN2-MW28	2900/3480/4060	145 CCT=4000K	120-277V	3000/4000/5000

L=AC120V-277V, M=AC120V-347V

EEE: CDM=Color selectable by switch / CDS=Color selectable by switch + sensor / CDE=Color selectable by switch + emergency driver / CSE=Color selectable by switch + sensor + emergency driver

Accessories



Photocell



Emergency river