

VECTOR Pulse

DVPL Up/Down Architectural Strip

The Vector Pulse Series is a highly competitive linear light. The creative quick-link buckle-type clamp allows the installer to make a tool-free continuous run. The unparalleled flexibility enables users to find the right light at different applications.

Client:	
Order#:	
Project:	
Type:	

FEATURES

- 115120 lm/W, 1,700lm10,800lm.
- Fieldadjustable Power and CCT.
- DirectIndirect flux ratio adjustable.
- Fast and seamless connection thanks to patent toolfree press lock design.
- Continuous run available.
- Multiple connection methods.
- Sensor and EM solution ready.



PERFORMANCE DATA

Model Number	Wattage Up	Wattage Down	CCT	Efficacy
DVPL-GEN2-2MW20	10W, 12W, 16W, 20W (selectable)	10W, 12W, 16W, 20W (selectable)	2700K, 3000K, 3500K, 4000K, 5000K (selectable)	>130 Lm/W
DVPL-GEN2-2MW20-W				
DVPL-GEN2-4MW40	20W, 24W, 32W, 40W (selectable)	20W, 24W, 32W, 40W (selectable)		
DVPL-GEN2-4MW40-W				
DVPL-GEN2-8MW80	40W, 48W, 64W, 80W (selectable)	40W, 48W, 64W, 80W (selectable)		
DVPL-GEN2-8MW80-W				

ORDERING INFORMATION


DVPL / GEN2 / _____ / _____ / _____ / _____
SERIES PHASE SIZE WATTAGE COLOR WARRANTY

FIXTURE SERIES	
DVPL	Vector Pulse Up/Down Architectural Strip
PHASE	
GEN2	Generation II: Multi Watt, Multi CCT
SIZE	
2	2 Feet
4	4 Feet
8	8 Feet
WATTAGE	
MW20	20W - 2 Feet Only
MW40	40W - 4 Feet Only
MW80	80W - 8 feet Only


COLOR	
-	Black (Standard)
W	White Finish
WARRANTY	
5	5 Year Warranty (included)
10	10 Year Warranty

Fast and seamless connection

Screwfree to remove endcover. Toolfree press lock connection.



Distributions



Direct/Indirect flux ratio adjustable


Direct	Indirect
100%	0%
70%	30%
50%	50%

Specifications

- UL Listing: Suitable for damp locations
- LEDs: Longlife, highefficiency, micropower LEDs
- Lifespan: Lumen Maintenance, L70 > 100,000 hours
- Housing and Lens: Sheet metal stamping, PC lens
- Ambient Operating Temperature:** 20°C (4°F) to 50°C (122°F)
- Driver: Driver includes dimming control wiring for 010V dimming systems. Flicker:10%.
- CRI:80**

Dimensions

Length




Height and Width



Size unit: inch(mm)

Mounting

Pendent mount, surface mount, wall mount, recessed mount are available with accessories(purchase separately).



Pendent mount



Surface mount



Recessed mount



Wall mount

Installation accessories


'L' connector




'T' connector




'X' connector




Power feed Suspension mount kit



Non-feed suspension kit, A type, 4" canopy



Non-feed suspension kit, B type, 2" canopy



Non-feed suspension kit, C type, ceiling nut



Power cord


5-core, STJ

6-core, STJ




Black Power cord available


T-Grid suspension kit



Surface mount & Wall mount kit



Recessed mount kit



DC sensor installation kit Option A, 2.5mm male audio connector sensor Option B, Quick-Connect Sensor, Popular styling



Option C, Quick-Connect Sensor, Classic mushroom-head profile



Soft DIY-cut diffuser
49.2' length per roll

