



GENERAL INFORMATION

The BPA-100 kW microwave generator is an air-cooled power supply for a 100 kW / 915 MHz magnetron. This power supply is designed based on modular interleaving technology to reduce input and output ripple as well as having the ability to protect the magnetron from over voltage and over current.

The BPA-100 kW autonomously manages the operating status of the magnetron and adjusts the filament voltage according to the input power of the magnetron and switches off the output when alarm events such as overcurrent or overvoltage of the magnetron occur.

FEATURES

- Very low energy discharge while heavy short circuit fault of magnetron
- Ability of the generator to continue operation at a lower power level in the event of a power supply module failure in the SMPS.
- Ability to replace a failed module with a functional one in less than 5 minutes.
- Ability to adjust of the anode voltage from 15 kV to 21 kV based on the magnetron performance chart to reach the optimized working point having max. efficiency/lifetime of Magnetron.
- Lower weight and lower output voltage ripples compared to the old transformer-based technology generators
- Air cooling
- Cutting edge interleaved resonance switching topology
- Adaptive to all 100 kW magnetrons made by different companies
- High efficiency up to 97%
- Fault tolerant SMPS
- High reliability (designed based on MIL-HDBK-338B and MIL-HDBK-217 standards)
- Low noise SMPS
- Adjusting the magnetron power from 10 kW to 100 kW in 0.5 kW steps
- Constructed using high quality power electronics and mechanical components all provided in Germany

SPECIFICATION

Electrical and Technical Data

	BPA100kW400	BPA100kW480	BPA100kW600	BPA100kW690
Input voltage efficiency	400 V _{AC} ±10 % up to 95 %	480 V _{AC} ±10 % up to 96 %	600 V _{AC} ±10 % up to 97 %	690 V _{AC} ±10 % up to 97 %
Input frequency		47 Hz to 63 Hz		
Output voltage adaptivity		15kV-21kV		
Anode current variation range		300 mA to 6000 mA		
Absolute maximum output power of Magnetron		100 kW		
Output voltage ripple		Less than 1%		
Anode current ripple		Less than 2%		
Active operating temperature		-20 to 50 °C		
HV Protections	Over temperature/ Over current/ Overvoltage/ Over load/ Under voltage/ Under load/ Short circuit			
Working humidity		20 ~ 90% RH non-condensing		
Storage temperature, humidity		-30 ~ +70, 10 ~ 95% RH non-condensing		
Withstand voltage		30 kV		
Dimension		2218*1221.5*1293 mm ³		