



GENERAL INFORMATION

Lab-scale microwave pyrolysis system for the conversion of biogenic feedstocks (e.g. microalgae, sewage sludge) into bio-oil, syngas, and biochar. Enables rapid, volumetric heating under controlled atmospheres (e.g. inert gas) with operating temperatures up to ~1000 °C and adjustable process parameters. Integrated product separation for solid, liquid, and gaseous fractions with options for condensation and gas analysis. Designed for flexible operation and process optimization, supporting scale-up towards industrial applications.

FEATURES

- Water-cooled
- High efficiency magnetron system
- Low noise SMPS with low ripple anode current for high reliability
- Hot air system
- Sensors for process monitoring (H₂ gas detector, IR camera for process control, inert gas control, temperature monitoring air in and out)

SPECIFICATION

Electrical and Technical Data

Output power, frequency	3 kW, 2.45 GHz
Supply voltage	3 x 400 V AC, +N+PE, 50 Hz
Total connected load	ca. 11 kVA
Current consumption	17 A

Cooling

Water cooling

Water flow	min. 35 l/min
Inlet water temperature	20 °C - 25 °C
Inlet pressure	min. 5 bar - 6 bar

Mechanical Data

Dimensions of housing (WxHxD)	2108 mm x 1971 mm x 1148 mm
-------------------------------	-----------------------------

