


EML-8017


Luminaire



Details




Schematic



Type	Explosion-proof exit sign luminaire
Mounting	Sidewall
Light source	50.000h operational time, 6000K color temperature
Warranty	5-years warranty
Dimensions	314mm x 188mm x 72mm
Housing color and material	White plastic
Cable connection	Max. 2.5mm ² cross-section solid or sleeved twisted wire
Operating mode	Non-maintained / Maintained
Constant nominal ambient temperature range	0 °C < Ta < 45 °C
EMLass	Zone 2

The EML-8017 is a one-sided, sidewall-mounted, explosion-proof LED exit sign designed for Zone 2 hazardous areas. Due to its IP65 rating, the luminaire is suitable for dry and wet locations (rest room, basement, garage) and for outdoor use as well. Pictogram's direction must be marked during the order.

The following pictograms can be selected:



Product name	System type	Main supply	Input current	Battery type/time	Product code
EML-8017 Slave/Con/MB	Conventional main battery	AC 120-240V	32mA	NIMH 600mA 1-3 h	-
EML-8017 Slave/Con/CB ACAC	Conventional central battery	AC 120-240V	24mA	-	-
EML-8017 Slave/Con/CB ACDC	Conventional central battery	AC/DC 120-240V	24mA	-	-
EML-8017 Slave/Con/CB/24V	Conventional central battery	DC 24-32V	80mA	-	-
EML-8017 Slave/MB	Addressable main battery	AC 120-240V	32mA	NIMH 600mA 1-3 h	-
EML-8017 Slave/RF/MB	Addressable wireless main battery	AC 120-240V	32mA	NIMH 600mA 1-3 h	300565
EML-8017 Slave/CB 24V	Addressable central battery	DC 24-32V	80mA	-	-
EML-8017 Slave/CB	Addressable central battery	AC 120-240V	24mA	-	-
EML-8017 Slave/CB AC-DC	Addressable central battery	AC/DC 120-240V	24mA	-	-