


# EML-5013


## Emergency Light



## Details




## Schematic



|  |   |
|--|---|
| Type                                       | LED emergency light   |
| Mounting                                   | Sidewall  |
| Light source                               | 50.000h operational time, 6000K color temperature                   |
| Luminous flux                              | 314 lm  |
| Warranty                                   | 5-years warranty  |
| Dimensions                                 | 192mm x 220mm x 65mm  |
| Housing color and material                 | White, metallic plastic   |
| Cable connection                           | Max. 2.5mm <sup>2</sup> cross-section solid or sleeved twisted wire |
| Operating mode:                            | Non-maintained  |
| Constant nominal ambient temperature range | -25°C < Ta < 50°C   |

Aesthetic LED safety light for recessing into the ceiling. It is available with round LED lens. It has a great effective range, its practical design makes it easy to install.

| Mounting height (m)    | 2,5   | 3    | 4    | 6    | 8    | 9    |
|------------------------|-------|------|------|------|------|------|
| Escape route min 1 lux | 3,813 | 4,15 | 4,31 | 4,35 | 4,39 | 3,75 |
| Transverse mounting    | 7,625 | 7,75 | 8,05 | 8,12 | 8,24 | 7,5  |



| Product name | System type | Main supply | Input current | Battery type/time | Product code |
|--------------|-------------|-------------|---------------|-------------------|--------------|
|--------------|-------------|-------------|---------------|-------------------|--------------|