


EML-D300


Luminaire



Details



Schematic



Type	Dynamic exit sign luminaire
Mounting	Sidewall, ceiling, flag
Light source	50.000h operational time, 6000K color temperature backlight, RGB matrix panel
Warranty	5-years warranty
Dimensions	337mm x 52mm x 179mm or 337mm x 52mm x 229mm
Housing color and material	Metal grey
Cable connection	Max. 2.5mm ² cross-section solid or sleeved twisted wire
Operating mode	Non-maintained / Maintained
Constant nominal ambient temperature range	0 °C < Ta < 45 °C

The EML-D300 is a dynamic LED exit light with a ceiling or sidewall-mounted design. It is recommended in buildings where more escape routes are available. In case of an emergency the control panel receives the information from the fire alarm center regarding the location of the fire, then the panel does inform the light about the right escape route to show.

Product name	System type	Main supply	Input current	Battery type/time	Product code
EML-D300 Slave/CB 24V	Wall mounted	Addressable central battery	DC 24-32V	196mA	-
EML-D300 Slave/CB 24V	Flag mounted, one sided	Addressable central battery	DC 24-32V	196mA	-
EML-D300 Slave/CB 24V	Flag mounted, two sided	Addressable central battery	DC 24-32V	370mA	-
EML-D300 Slave/CB 24V	Ceiling mounted, one sided	Addressable central battery	DC 24-32V	196mA	-
EML-D300 Slave/CB 24V	Ceiling mounted, two sided	Addressable central battery	DC 24-32V	370mA	-
EML-D300 Slave/CB	Wall mounted	Addressable central battery	AC 120-240V	37mA	-
EML-D300 Slave/CB	Flag mounted, one sided	Addressable central battery	AC 120-240V	37mA	-
EML-D300 Slave/CB	Flag mounted, two sided	Addressable central battery	AC 120-240V	70mA	-
EML-D300 Slave/CB	Ceiling mounted, one sided	Addressable central battery	AC 120-240V	37mA	-
EML-D300 Slave/CB	Ceiling mounted, two sided	Addressable central battery	AC 120-240V	70mA	-
EML-D300 Slave/CB AC-DC	Wall mounted	Addressable central battery	AC/DC 120-240V	37mA	-
EML-D300 Slave/CB AC-DC	Flag mounted, one sided	Addressable central battery	AC/DC 120-240V	37mA	-
EML-D300 Slave/CB AC-DC	Flag mounted, two sided	Addressable central battery	AC/DC 120-240V	70mA	-
EML-D300 Slave/CB AC-DC	Ceiling mounted, one sided	Addressable central battery	AC/DC 120-240V	37mA	-
EML-D300 Slave/CB AC-DC	Ceiling mounted, two sided	Addressable central battery	AC/DC 120-240V	70mA	-