


## EML-6016


## Emergency Light



## Details




## Schematic



Type	LED emergency light
Mounting	Sidewall, ceiling
Light source	50.000h operational time, 6000K color temperature
Luminous flux	24V: 745 lm CON/MB: 567 lm
Warranty	5-years warranty
Dimensions	337mm x 170mm x 62mm
Housing color and material	White plastic
Cable connection	Max. 2.5mm <sup>2</sup> cross-section solid or sleeved twisted wire
Operating mode:	Non-maintained

Thanks to IP65 protection it is suitable in dry and wet locations (rest room, basement, garage, etc.) and for outdoor use as well.

Mounting height (m)	2,5	3	4	6	8	10	15
Transverse mounting	11	12.2	14.4	16.2	17.5	18.2	4.7
Escape route min 1 lux	4.7	5.1	5.7	6.8	6.8	6.1	5.6
Axial mounting	11	12.2	14.4	16.2	17.5	18.2	4.7
	4.7	5.1	5.7	6.8	6.8	6.1	5.6



Product name	System type	Main supply	Input current	Battery type/time	Product code
EML-6016 Slave/Con/MB	Conventional main battery	AC 120-240V	21mA	NIMH 600mA 1 h	300346
EML-6016 Slave/Con/MB	Conventional main battery	AC 120-240V	21mA	NIMH 2400mA 3 h	-
EML-6016 Slave/Con/CB ACAC	Conventional central battery	AC 120-240V	31mA	-	300423
EML-6016 Slave/Con/CB ACDC	Conventional central battery	AC/DC 120-240V	31mA	-	-
EML-6016 Slave/Con/CB/24V	Conventional central battery	DC 24-32V	235mA	-	-
EML-6016 Slave/MB	Addressable main battery	AC 120-240V	21mA	NIMH 600mA 1 h	300198
EML-6016 Slave/MB	Addressable main battery	AC 120-240V	21mA	NIMH 2400mA 3 h	300059
EML-6016 Slave/RF/MB	Addressable wireless main battery	AC 120-240V	21mA	NIMH 600mA 1 h	-
EML-6016 Slave/RF/MB	Addressable wireless main battery	AC 120-240V	21mA	NIMH 2400mA 3 h	-
EML-6016 Slave/CB 24V	Addressable central battery	DC 24-32V	235mA	-	300302
EML-6016 Slave/CB	Addressable central battery	AC 120-240V	31mA	-	300310
EML-6016 Slave/CB ACDC	Addressable central battery	AC/DC 120-240V	31mA	-	-