

## 1. Identification

Product Name:	Watermarque 2K Topcoat Satin Matt Hardener
Recommended use:	Hardener component for Watermarque 2K Topcoat Resin
Supplier:	Uroxsys Ltd
Street Address:	2 Stonedon Drive, East Tamaki, Auckland
Telephone Number:	+64 9 2740808 (8.00am to 5.00pm, Monday to Friday)
Emergency Telephone:	After hours phone CHEMCALL 0800 243622 (or +64 4 9179888)
National Poison Information Centre	0800 POISON (764766)
Date of issue	17 <sup>th</sup> March 2025

## 2. Hazards identification

### GHS classification of the substance/mixture:

Classified as Hazardous according to Hazardous Substances (Hazard Classification) Notice 2020  
Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433: 2020  
Transport of Dangerous Goods.



Flammable liquid category 4, Acute toxicity Inhalation, Category 4, Sensitization of the skin category 2, STOT SE Category 3 (respiratory tract irritation), Hazardous to the aquatic environment chronic Category 3

EPA Approval: HSR002657  
Surface Coatings and Colourants (Combustible) Group Standard 2020  
3.1D, 6.1D(i), 6.1E (respiratory tract irritant), 6.5B, 9.1C

### Signal Word:

WARNING

### Hazard Statements:

H227: Combustible liquid.  
H317: May cause an allergic skin reaction.  
H332: Harmful if inhaled.  
H335: May cause respiratory irritation.  
H412: Harmful to aquatic life with long lasting effects.

### Precautionary Statements – Prevention:

P102: Keep out of reach of children.  
P103: Read label before use.  
P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P261: Avoid breathing fume/gas/mist/vapours/spray.  
P271: Use only outdoors or in a well-ventilated area.  
P272: Contaminated clothing should not be allowed out of the workplace.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/eye protection/face protection.

### Precautionary Statements – Response:

P101: If medical advice is needed, have product container or label at hand.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P370+P378: In case of fire use water fog, foam, dry agent (carbon dioxide, dry chemical powder).

### Precautionary Statements – Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

P403+P233: Store in a well-ventilated place. Keep container tightly closed

P405: Store locked up.

### Precautionary Statements – Disposal:

P501: Do not contaminate storm water with product or product washing. Do not pour product down the drain. Unwanted product should be reacted with appropriate quantity of resin and brushed out on newspaper, allowed to cure and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to cure. When cured, recycle the container via recycling programmes. Disposal of empty paint containers via domestic recycling may differ between local authorities. Check with your local council first.

## 3. Composition/information on ingredients

Material	CAS No	%
Hexamethylene diisocyanate homopolymer	160994-68-3	> 60
Dipropylene glycol dimethyl ether	111109-77-4	20 – 40
Hexamethylene-1,6-diisocyanate	822-06-0	< 0.15

## 4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:** If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**PPE for First Aiders:** Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

## 5. Fire-fighting measures

**Hazchem Code:** Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Combustible liquid.

**Fire fighting further advice:** On burning or decomposing may emit toxic fumes. Fire fighters to wear self contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. Accidental release measures

**Emergency procedures:** If contamination of sewers or waterways has occurred advise local emergency services.

**Methods for containment & clean up:** Clear area of all unprotected personnel. Clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect in properly labeled containers.

**Small spills:** Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

**Large Spills:** If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

## 7. Handling and storage

**Handling:** Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

## 8. Exposure controls/personal protection

Occupational Exposure Limits:	No value assigned for this specific material by Worksafe NZ. However, NZ Workplace Exposure Standard(s) for constituent(s): Isocyanates, all (as-NCO) (sen):TWA 0.02 mg/m <sup>3</sup> ; STEL 0.07 mg/m <sup>3</sup> . These values apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.
Biological Limit Values:	No Biological Limits allocated.
Engineering Control Measures:	Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use.
Personal Protective Equipment:	Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If spraying or inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.
Hygiene measures:	Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or

smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9. Physical and chemical properties

Physical state:	White Liquid
Odour:	Not established
Odour Threshold:	not established
pH:	not applicable
Melting/Freezing point:	not established
Boiling point/boiling range:	ca.175 °C
Flash point:	65 °C
Flammability (solid, gas):	not applicable
Upper/lower flammability or explosive limits:	not established
Vapour pressure:	not established
Vapour density:	not established
Specific gravity:	1.0
Solubility:	Dispersible in water .
Partition coefficient (n-octanol/water):	not established
Auto-ignition temperature:	not applicable
Decomposition temperature:	not established
Viscosity:	not established
Particle characteristics:	not established

## 10. Stability and reactivity

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

## 11. Toxicological information

Data sourced from raw material SDSs and/or CCID.

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Effects

**Inhalation:** Material may be an irritant to mucous membranes and respiratory tract.

**Skin contact:** Contact with skin will result in irritation. Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Eye contact:** An eye irritant.

### Acute toxicity

Hexamethylene-1,6-diisocyanate: Oral LD50 (mouse) 350 mg/kg, Dermal LD50 (rabbit): 593 mg/kg, Inhalation LC50: 15 mg/m<sup>3</sup>/4hours

**Inhalation:** This material has been classified harmful if inhaled for acute inhalation exposure. LC50 (rat) 1.5mg/l for Hexamethylene diisocyanate homopolymer.

**Skin contact:** This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): LD50 > 2,000 mg/Kg bw

**Ingestion:** This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): LD50 > 2,000 mg/Kg bw

**Corrosion/Irritancy:** Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has not been classified as a respiratory sensitiser.

Skin: May cause sensitization by skin contact

**Aspiration hazard:** This material has been classified as not an aspiration hazard.

**Specific target organ toxicity (single exposure):** This material has been classified as not a specific hazard to target organs by a single exposure.

Chronic Toxicity

**Mutagenicity:** This material has been classified as not a mutagen.

**Carcinogenicity:** This material has been classified as not a carcinogen.

**Reproductive toxicity** (including via lactation): This material has been classified as not a reproductive toxicant.

**Specific target organ toxicity (repeat exposure):** This material has been classified as respiratory tract irritant.

## 12. Ecological information

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

**Long-term aquatic hazard:** This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log Kow < 4.

**Ecotoxicity:** No information available.

**Persistence and degradability:** No information available.

**Bioaccumulative potential:** No information available.

**Mobility:** No information available.

## 13. Disposal considerations

Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

Empty container: Do not contaminate storm water with product or product washing. Do not pour product down the drain. Unwanted product should be reacted with appropriate quantity of resin and brushed out on newspaper, allowed to cure and then disposed of via waste collection. Empty containers should be left open in a well-ventilated area to cure. When cured, recycle the container via recycling programmes. Disposal of empty containers via domestic recycling programmes may differ between local authorities. Check with your local council first.

## 14. Transport information

Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433: 2020 Transport of Dangerous Goods.

### Road and Rail Transport

Not Classified as Dangerous Goods by NZS 5433 Transport of Dangerous Goods on Land.

### Marine Transport

Not Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

### Air Transport

Not Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

## 15. Regulatory information

EPA Approval: HSR002657 Surface Coatings and Colourants (Combustible) Group Standard 2020

Certified Handler : Not required

Tracking: Not required

All ingredients are on the New Zealand Inventory of Chemicals (NZIoC), or exempt.

## 16. Other information

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.

This version replaces all previous versions.

### Glossary

EPA: Environmental Protection Authority (NZ)

WES: NZ Work Exposure Standard

TWA: Time Weighted Average

STEL: Short Term Exposure Limit

CCID: Chemical Classification & Identification Database (EPA)

END OF SDS