## **Bittel**

A Compact Two-Way L- Band Communicator



Bittel 3.0

Bittel is a compact, high-performance two-way L-Band satellite communicator. Designed for portability, it ensures reliable connectivity beyond the line-of-sight range of cellular and LMR networks.


On land, at sea, or in the air, in both rural and urban environments, Bittel delivers exceptional communication capabilities - without requiring a clear sky or direct line of sight to the satellite.


Leveraging Inmarsat's global GEO satellite coverage, Bittel provides users worldwide with a real-time, essential connectivity solution - compact, flexible, and ready to be carried or mounted anywhere, anytime, even in the harshest conditions.

Powered by advanced narrowband core technology, Bittel functions as a standalone communication device within a tactical network. It can also be integrated as a chipset into various systems, supporting a wide range of applications across both tactical and global networks, ensuring seamless and reliable connectivity everywhere.

	Bittel Specifications		
Battery Type	Rechargeable, built-in lithium-ion battery		
Battery Life	6-24 hours *(depends on device settings)		
IP Rating	IP67		
RF Output (PTT)	2 Watts		
Operating temperature range	-20° to 60°C (-4° to 140°F)		
Charging temperature range	6-24 hours		
Physical	0° to 45°C (32° to 113°F)		
Wireless Interface	99mmx60mmx20mm, 200 grams		
Wireless Interface	Bluetooth (ver 4.2)		
Wire Interface (DC Power + Comm)	USB Type C		

Bittel Features				
*	<b>⊕</b>	@	•	
Global Inmarsat® Satellites	Two-way text messaging	Emergency SOS	GPS (Blue Force Tracking)	
≒		*		
Pairs with mobile devices	User interface by mobile app	Wireless connectivity by Bluetooth		











## Contact us

info@commcrete.com https://commcrete.com