

TECHNICAL DATA SHEET

C305HC


SPECIFICATIONS

Part Number	C305HC
BCI Group	902
Tension	6 Volts
Technology	Wet Acid
Acid Density	1.280
Capacity @20HR	330 Ah
Reserve Capacity	760 min. @25 amp.
Life Cycles	700 cycles at 80% DOD
Terminal Type	Dual, auto post + stud 5/16"
Terminal Torque	11-14.7 N*m (111-150 KGf*cm)
Container Material	Polypropylene
Integrated Hydrometer	Yes
Space between cells	3.37" (3 3/8"), 86 mm
Classification	UN2794




DIMENSIONS

Length	11 5/8" (296 mm)
Width	6 15/16" (176 mm)
Case Height	13 1/2" (343 mm)
Overall Height	14 7/16" (366 mm)
Weight	92.6 lbs (42 Kg)

INTEGRATED HYDROMETER




DRAWINGS




CHARGE INDICATOR	SPECIFIC GRAVITY (25°C)	OPEN CIRCUIT VOLTAGE	CHARGING STATE (%)
GOOD STATUS (65%+)	1.285	6.405	100
	1.265	6.345	90
	1.245	6.285	80
	1.225	6.225	70
	1.205	6.165	60
CHARGING NECESSARY STATUS (65%-)	1.185	6.105	50
	1.165	6.045	40
	1.145	5.985	30
	1.125	5.925	20
	1.105	5.865	10

CHARGE / DISCHARGE PERFORMANCE CURVES


Charging Characteristics (25°C, 77°F)




Cycle life in relation to depth of discharge



Relationship of OCV and SOC (25°C, 77°F)



Temperature effects on capacity



CHARGE METHOD

Initial Charge:

- 0.1C₂₀(A) charging 15 h
- 0.05C₂₀(A) charging 10 h

The temperature of the battery should be below 50°C during charging.

Float Voltage:

- 2.25 V/cell, 6.75 V

Equalizing Charge:

- 8.10 V

Supplement Charge:

- Charging at a constant voltage of 7.35~7.5 V/cell and a limited current 0.25C₂₀(A) until the electrolyte density up to 1.280g/cm³ (30°C) and the current not change for 3 hours.
- Charge with constant current 0.1C₂₀(A) until the voltage between 7.8~8.4 V/cell, and voltage maintains for 3 hours and not change.

Two method optional.

RECYCLING

- 99% recyclable

CYCLONE, all rights reserved. CYCLONE is not liable for damages that may occur from any information provided in or omitted from this publication, under any circumstances. CYCLONE reserves the right to make changes or adjustments to this publication at any time without notices or obligations.

CYCLONE
HD SERIES • DEEP CYCLE