



DEMOUNTABLE CONCEPTS

• AMERICA'S SWAP BODY •



Line-Haul Trailer Leg Supplement

Toll Free: (844) 364-4021

Web: demount.com

An improperly secured container that falls off a trailer can result in injury or death.

It is the driver's responsibility to make sure that the containers are properly locked onto the trailer before each trip.



Be sure all people are clear of the trailer and containers when mounting and demounting.

Do not operate equipment without proper training from Demountable Concepts or an authorized training provider.

- Report any defect or problem on your daily driver inspection report and to your supervisor.
- Read and understand all safety labels on the equipment.
- Failure to check that trailer is centered and straight when backing under or pulling out is the primary cause of damage.

When demounting containers:

- Be sure all legs are in proper position with leg pins locked.
- Light plugs must be disconnected.
- Containers must be unlocked.

When transporting the containers on trailer:

- The containers must be locked in place -- Visually confirm by checking locking hooks and levers before each trip.
- All legs must be stored inside the containers and locked in place.
- Light plugs must be connected.



1. On the passenger-side of the front container begin setting the legs.

When working with legs:

- **Always wear gloves for hand protection.**
- **Never put fingers into the holes in the legs.**



2. Start with the front leg:

- Release the secondary leg locking mechanism.

Pivot it until it is no longer in front of the foot pad.



3. Rotate the handle portion of the leg pin upward and slide it out of the leg and retainer.

Note: The key on the pin's side must be properly aligned to pass through the key-way in the retainer.



4. Grab the leg by the bottom of the footpad and pull it out all the way.
 - Gently lower the leg.
Do not drop it.
 - If necessary, the bottom section of the leg is adjustable.



5. Insert the leg pin through the brace and leg. Swivel the handle down to secure it.



6. Push the leg assembly into the housing until the top brace touches the container side rail.



7. Repeat this procedure for all legs on both containers.
 - Check to be sure all leg pins are fully inserted and securely in place.

Be sure you set and secure all 8 legs.



1. On the passenger-side front leg, rotate the handle portion of the leg pin upward and slide it out to release the leg brace.

Note: The key on the pin's side must be properly aligned to pass through the key-way in the leg and brace.



2. Lift the vertical portion of the leg to a horizontal position and slide the entire leg into the leg housing.



3. Be careful not to pinch your fingers between the leg's footpad and the housing.
 - We recommend making a fist with both hands and pushing against the bottom of the footpad to slide in the leg.



4. Place the leg locking pin through the leg retainer and the leg.
 - Engage the secondary locking mechanism by swiveling it in front of the foot pad.



5. Work your way around the trailer to the driver side until all eight legs are stored and secured.



DEMOUNTABLE CONCEPTS

• AMERICA'S SWAP BODY •

Watch the Training Video



Line-Haul Trailer
Leg Supplement

Contact Info: US, Canada & Mexico

Toll Free: (844) 364-4021

Web: demount.com