

I'm not a bot



Britax boulevard 70 convertible car seat manual

Britax boulevard 70 g3. Britax boulevard 70-g3 manual. Britax romer i-size установка. Britax romer dualfix установка. Britax boulevard manual.

Boulevard™ 70 CS User Guide: Read this guide carefully before installing the child seat. Store it in the pocket behind the cover (check the features pages for reference). Here's what you'll find: ****Safety First**** * Important notices about safety * Warnings and cautions * Certification and registration information ****Installing Your Child Seat**** * Information on compatible vehicle seat belts and seating positions * Incompatible vehicle seat belts to watch out for * How to adjust the harness height and buckle position ****Using the Child Seat Features**** * Click & Safe Snug Harness Indicator: ensuring a secure fit * Adjusting the buckle and releasing it safely * Using the chest clip, lock-offs, and infant body pillow * Recline positions and LATCH installation Installation & Use Instructions38 Forward-Facing Installation: Forward-Facing Child Restraint42 LATCH Installation: Lower Anchorage Child Restraint42 Lap-Shoulder Belt Installation: Lap Shoulder Child Restraint46 Aircraft Installation: Air Travel Child Restraint Installation54 Securing Your Child: Tips & Tricks for Safe Child Restraint Use55 Care and Maintenance: How to Keep Your Child Restraint in Top Condition58 Tips and Troubleshooting: Common Issues and Solutions67 Warranty Information: What's Covered and for How Long68 Warning! Deadly Consequences Can Occur If68 * Use only in rear-facing position with infants under 20 lbs (9.1 kg) or less than 1 year old. * Only use with children weighing between 5-70 lbs (2.3 - 31.8 kg) and whose height is 49 in. (124.5 cm) or less. * Always snugly adjust the belts around your child, allowing no slack; straps should lie in a straight line without sagging. * Secure top anchorage strap provided with this child seat. * Use vehicle's child restraint anchorage system if available, or secure with vehicle seat belt. * Follow all instructions on this child restraint and written instructions located behind the cover. * Register your child restraint with manufacturer. * This child seat must be reclined to position 3 when installed rear-facing (see page 22). * Use inner buckle slot when installing rear-facing; outer buckle slot for forward-facing installations above 30 lbs (13.6 kg) or if buckle is under the child in the inner position. * When installing forward-facing, this child seat must be in position 1 or 2 (see page 22). * HUGS chest pads must be used in forward-facing mode; removal optional for rear-facing mode. * Discontinue use of this child seat if it shows signs of deterioration or hidden damage to prevent injury. * Do not use if involved in a moderate or severe crash (see page 4). Check the Serial Number and Manufacture Date Label on child seat (page 15). ****Child Seat Safety Guidelines**** This child seat should not be used at home, in boats, or other non-certified applications. According to NHTSA statistics, parents should install the back seat as the safest location for a properly installed child seat. Please study Vehicle Seating Positions on page 13 and consult your vehicle owner's manual. ****Important Installations**** Secure this child seat even when it is not occupied, as an unsecured child seat may injure vehicle occupants in a crash. When using in a vehicle with air bags, refer to your vehicle owner's manual for installation instructions and precautions. ****Usage Tips**** Never use the harness adjuster strap to lift or carry this child seat, as it can cause damage. Always carry this child seat by its shell or tether straps. The primary protection for occupants of a vehicle in a collision is the body of the vehicle itself; a child seat will not protect a child when a vehicle is seriously impacted. ****Maximum Weight Rating**** Refer to your vehicle owner's manual or contact the manufacturer for the maximum weight rating for their lower anchors. Use vehicle seat belt (not lower connectors) for installations with children who weigh more than the vehicle lower anchor limit, assuming a 40 lb (18.1 kg) child as the limit. ****Safety Information**** Important Notes: * Verify that the child seat is securely installed and the harness is properly adjusted around the child each time it is used. * Discontinue use of this child seat if it has been in a moderate or severe crash. * Adjust the harness to fit the clothes the child is wearing. Remove bulky coats and/or jackets before putting the child in child seat. * Cover the child seat when the vehicle is parked in direct sunlight to prevent metal parts from becoming hot enough to burn a child. * Store the child seat in a safe place when it is not being used, avoiding heavy objects on top of it. * Do not leave children alone in a vehicle, even for a short time. * Do not, except as described in this booklet, attempt to disassemble any part of the child seat. Do not leave loose objects in a vehicle, as they can cause injuries during sudden stops. Also, do not play with this child seat or raise it off the vehicle's seat without following instructions. This child restraint system conforms to all applicable Federal Motor Vehicle Safety Standards and is certified for use in motor vehicles and aircraft. To be reached in case of recall, you must register this restraint by sending your name, address, email (if available), model number, and manufacturing date to Britax Child Safety, Inc. ****Child Seat Usage Information**** * All infants should ride rear-facing until they reach 1 year old or weigh 20 lbs. * A snug fit can be achieved using an infant positioning insert if the child is under 12 lbs and the lowest harness slots fall above their shoulders. * Children should be secured with a harness system until they exceed the specified weight or height limits, and Britax recommends rear-facing to the highest weight or height specified. ****Rear-Facing Requirements**** * Rear-facing use is only for children who meet all of the following requirements: * Weigh between 5 and 40 lbs * Be securely harnessed within these requirements the child's head must be at least 1 inch below the top of the car seat, and when putting on the harness straps they should rest just above or slightly below the kid's shoulders; see harness height adjustment on page 18. For kids who are forward-facing, make sure they're over one year old, weigh between 20-70 pounds (9.1-31.8kg), are no taller than 49 inches (124.5 cm) and when their ears are below the top of the seat or the harness straps are above their shoulders, when using position 2 it might be necessary to adjust the harness higher; see harness height adjustment on page 18 again. also, remember that child seats are only compatible with certain types of vehicle seat belts, so check your car manual for more info. If you have an ALR (automatic locking retractor) with a sliding latch plate, make sure it locks once you've pulled the belt out at least 24 inches (61 cm), if you have an ELR (emergency locking retractor), ensure the latch plate and vehicle belt lie flat against the child seat to prevent unlocking. switchable retractors need to be set to ALR mode or use lock-offs for safe usage with a child seat. b The child seat features an Automatic Locking Retractor that only locks in emergency situations like sudden stops or crashes. Note: This type of belt requires using the lock-offs built into the seat for rear-facing and forward-facing installations. See page 21 for information on using the lock-offs. Lap Belt 5. ALR (Automatic Locking Retractor) a Has a latch plate sewn into the webbing. Latch plate b Stops the belt from being pulled out again once the webbing has been pulled at least 24 inches. Tightens by feeding the webbing back into the retractor. Vehicle Compatibility Incompatible Vehicle Seat Belts WARNING! The following types of vehicle seat belts are not compatible with this child seat: lap-shoulder belts with top or bottom anchor points on the vehicle door, inflatable lap-shoulder belts, motorized, automatic vehicle seat belts, and lap belts forward of the vehicle seat bight. Vehicle Seating Positions Vehicle Compatibility WARNING! Do not place the child seat rear-facing in the front seat of a vehicle with a passenger air bag unless deactivated. DEATH or SERIOUS INJURY can occur. The back seat is the safest place for children 12 and under. Some vehicles may have no seating positions compatible with this child seat. To ensure your child's rear-facing seat is secure, follow these steps to tighten the harness: First, remove any bulky clothing from your child. Next, check that the harness is at the correct height and remove slack from around their upper thighs and between the chest pads and buckle. Then, pull up on the adjuster strap until you hear a click - this indicates the harness is snug enough. Double-check by attempting to pinch excess webbing. Remember, a snug strap should lie in a straight line without sagging or pressing on your child's flesh. Now, for harness height adjustment: loosen the harness and lift the adjuster lever before squeezing the harness height adjuster and sliding it into position. Make sure it locks in place. Always keep the harness straps at or below your child's shoulders when facing rearward and above their shoulders when facing forward. When adjusting the buckle position, always use the inner slot for rear-facing mode and never leave the buckle in the adjustment slot. Remember to follow detailed instructions on securing your child, as found on pages 55-57. 1 Put the tongue into the buckle one by one. - When it's done, you'll hear a click. 2 To put on the child seat, do these steps: - Open and press the chest clip together. - Position the clip around your arm hole. - Pull the clips apart to fasten. - Never forget to clean the buckle regularly for smooth operation.