


Description

Anti-Ligature Unsprung Lever Set at 45 Degrees, 63mm Rose



Technical Features

Function & Operation	Lever handle designed to remove the ligature point provided by normal door hardware
Summary of Features	Anti-ligature lever, set at 45 degrees on a 63mm rose, that is designed so that when pressure is applied, or a ligature is attached, the lever drops down to 90 degrees, causing a ligature to slip off. Suitable for doors 44 to 54mm thick. Through fix rose into M4 back fix rose.

Options n/a

Dimensions

Dimensions 63mm diameter rose and fixings at 38mm centres

Finishes

Finishes Available Satin Stainless Steel or Aluminium

Certification

European Norm	No Harmonised European Norm
Product Classification	n/a (No Harmonised European Norm)
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)
Certifire No.	n/a (No Harmonised European Norm)
Declaration of Performance	n/a (No Harmonised European Norm)
Other Test Evidence	n/a

BIM Assist™

BC(A)R Assist™*

Guarantee

5 Year

Last Reviewed

30/01/2020

* ROI Only

ANTNS7/63 Satin Stainless Steel

Description

Anti-Ligature Unsprung Lever Set at 45 Degrees, 63mm Rose



Specification Text

LEVER HANDLES

- Manufacturer: DORTEND
- Product reference: ANTNS7/63
- Style: Anti-Ligature Lever Set at 45 Degrees
- Size: 63mm diameter rose and fixings at 38mm centres
- Material/ finish: [SPECIFY FINISH]
- Mounting: Bolt through fixings
- Additional requirements: Unsprung

