

TUFFGRIP UNLIMITED

UNLIMITED MOISTURE VAPOR BARRIER, WOOD ADHESIVE

RH	pH	MVER	OPEN TIME	WORKING TIME	CURE TIME	LIGHT TRAFFIC	HEAVY TRAFFIC	STC	IIC
									
100%	NTR* 5-14	NTR*	0 MIN	45 MIN	12 HRS	6 HRS	6 HRS	62 dB**	68 dB**

APPROVED FLOORING TYPES

- WOOD:** Acrylic Infused Plank, Bamboo, Cork (flooring, cork-backed hard surface, underlayment) Hardwood (engineered, parquet, solid)
- RESILIENT:** Rubber (crumb)

WHY USE

- Unlimited moisture protection (porous slab)
- Cost savings potential
- No moisture or pH testing required
- Permanent, waterproof bond
- Solvent and isocyanate-free
- Non-staining and easy to clean
- 1-step installation (no stirring/mixing)
- High-strength, elastomeric membrane
- Rapid occupancy times
- Faster construction timeline
- Sound control (IIC, STC)
- Warranted over cutback residue (see TDS)
- Protects flooring from alkali attack
- Extremely low VOC, extremely low odor
- Antimicrobial technology



CERTIFICATIONS



COVERAGE: 20-70 ft²/gal
AVAILABLE IN: 4 gal
SHELF LIFE: 1 year