










TUFFGRIP PS-99

FIRM-SET MODIFIED TRANSITIONAL PSA

RH	pH	MVER	FLASH TIME	WORKING TIME	CURE TIME	LIGHT TRAFFIC	HEAVY TRAFFIC	ROLLING LOADS
								
99%	5-12	12 lbs	30-60 MIN*	12 HRS	12 HRS	0 MIN*	24 HRS	48 HRS

APPROVED SUBSTRATES & SURFACES

- APA underlayment grade plywood and OSB
- Association grade particleboard
- Cement backer board
- Cementitious and anhydrite screeds
- Concrete and radiant heated subfloors that do not exceed 85°F (30°C)
- Well-bonded residue from cutback adhesives
- Well-bonded residue from multipurpose, latex, and pressure sensitive adhesives

WHY USE

- Aggressive tack, fast grabbing
- High moisture tolerance
- High-strength, water-resistant bond
- Elastomeric bond
- Repositionable installation
- Immediate access for light traffic
- Handles heavy rolling loads
- Attractive price point
- Installs multiple flooring types
- 12 hours of working time
- Simple installation
- Plasticizer migration resistance
- Low VOC, extremely low odor
- Antimicrobial technology

CERTIFICATIONS



COVERAGE: 90-350 ft²/gal
AVAILABLE IN: 1 and 4 gal
SHELF LIFE: 2 years