

Emotion Print

ECO cert | Acoustic design.





Acoustic panel made of recycled polyester fiber from the ECO line by ECOcero, ECOwall Emotion model, printed family on panel and beveled, standard design, with dimensions 2340x1170 mm, thickness 12 mm. Includes fixing system using ECOcero brand adhesive for direct attachment to the support. Available in catalogue image colors. CE marked, Euroclass B-s1, d0 fire reaction. Compliance with low VOC emissions specifications. GOLD certification in LEED and BREEAM, GLOBAL RECYCLED STANDARD, and OEKO-TEX STANDARD 100.

Composition	Recycled polyester fiber
Maximum dimension	2340x1170 mm / Custom
Thickness	12 mm
Weight	6,6 kg
Surface density	2,4 kg/m ²
Absorption without cavity	ISO: $\alpha_w=0,30$. ASTM: NRC=0,45
Absorption with 50 mm cavity	ISO: $\alpha_w=0,75$. ASTM: NRC=0,8
Absorption with 200 mm cavity	ISO: $\alpha_w=0,90$. ASTM: NRC=0,85
Fire resistance	B-s1,d0. Fire retardant. CTE for public use premises
Thermal resistance	0,300 (m ² ·K/W)
Thermal conductivity	$\lambda=0,040$ (W/m·K)
Thickness tolerance	± 1 mm
Cutting tolerance	± 2 mm
Installation	Without construction work, easy and fast. Fixed with adhesive or suspended using anchors, both provided by ECOcero
Cleaning	For surface cleaning, it is recommended to spray an alcoholic solution (75%). In case of dust or lint, use a duster or vacuum cleaner. In case of heavy soiling, treat the material with hydrogen peroxide. Do not rub.

ECO Line Certificates (PET)



LEED® Certificate (Pass)



BREEAM® Certificate (Exemplary level)



Green Building Council USGBC



Antifungal Certificate



VOCs Certificate (A+ classification)



Acoustic Absorption Certification



CE Certified (EN 15102:2007 + A1:2011)



GLOBAL RECYCLED STANDARD Certificate
(Minimum 60% Post-consumer)




OEKO-TEX STANDARD 100 Certificate



Recycled Content Certification

Print




EW249



EW250




EW251



EW252



EW253



EW254

Get inspired:



