

Square

ECO cert | Acoustic design.





Acoustic panel made of recycled polyester fiber from the ECO line by ECOcero, model ECObasic Rectangle, catalog design, with dimensions of 585x1170 mm and a thickness of 24 mm. Includes adhesive system by ECOcero contact glue for direct attachment to the surface. Available in 2 base colors (white and black), with the option of painting in any color from the RAL or NCS color charts. CE marked, Euroclass B-s2, d0 fire reaction rating. Complies with low VOC emission specifications. Certified GOLD in LEED and BREEAM, GLOBAL RECYCLED STANDARD, and OEKO-TEX STANDARD 100.

Composition:	Recycled polyester fiber
Maximum Dimension:	585x1170 mm / Custom
Thickness:	24 mm
Weight:	2,7 kg
Surface Density:	4,0 kg/m ²
Absorption without cavity:	ISO: $\alpha_w=0,50$. ASTM: NRC=0,70
Absorption with 200 mm cavity:	ISO: $\alpha_w=1,00$. ASTM: NRC=0,95
Fire Resistance:	B-s2,d0.Fire-resistant. CTE for public gathering spaces
Thermal Resistance:	0,600 (m ² ·K/W)
Thermal Conductivity:	$\lambda=0,040$ (W/m·K)
Thickness Tolerance:	± 1 mm
Cutting Tolerance:	± 2 mm
Installation:	No construction work required, quick and easy installation / Attached with adhesive or suspended using anchors, both supplied by ECOcero
Cleaning:	For surface cleaning, spray with an alcohol solution (75%). For dust or lint, use a feather duster or vacuum cleaner. For heavy soiling, treat the material with hydrogen peroxide. Do not rub.

ECO Line Certificates (PET):



LEED® Certificate (Pass)



BREEAM® Certificate (Exemplary level)



Green Building Council USGBC



Antifungal Certificate



VOCs Certificate (A+ classification)



Acoustic Absorption Certification



CE Certified (EN 15102:2007 + A1:2011)



GLOBAL RECYCLED STANDARD Certificate
(Minimum 60% Post-consumer)



OEKO-TEX STANDARD 100 Certificate



Recycled Content Certification

Colors



Black	Polar White	N
ECO-127	ECO-104	C
NCS: S 9000-N	NCS: S 0502-B50G	NCS

N: Name
C: Color code
NCS: NCS code

Beyond the 16 colors of the ECO line, with its soft pastel tones designed to evoke emotions, we offer custom paint options in any color from the RAL and NCS palettes. Our special paint ensures perfect sound absorption and acoustic conditioning.

Get inspired:





