



# Altus XE5318GTSv2

Big problems need big solutions



### Overview

Graphics Processing Units (GPUs) have quickly established themselves as the computing tools of the future. As the growth rate of Central Processing Unit (CPU) speeds slows down, GPUs can offload compute-intensive functions from CPUs and accelerate your time-to-results.

The Penguin Solutions® Altus® XE5318GTSv2 server is built on the latest technology offering the maximum amount of interconnected GPUs to process intense amounts of data with the least amount of latency.

## **Key Features**

- Dual AMD EPYC™
  9005/9004 processors
- Up to 24 DDR5-6400 MT/s memory modules to deliver speed and efficiency for data-intensive workloads
- Storage density for up to 8x 2.5" hot-swap drive bays with SATA and NVMe support
- Supports up to 8 x Nvidia SXM5 GPUs with Dedicated GPUDirect RDMA NICs

## **Technical Specifications**

Form Factor	
Form Factor	5U Rackmount
Processors	
Processor Number	2
Processor Type	AMD EPYC™ 9005/9004 series
Maximum TDP	400W, cTDP 500W
Motherboard	
Chipset	SoC
Board Management	
BMC Chipset	ASpeed AST2600
Dedicated BMC Interface	RJ45
IPMI 2.0	Yes
Virtual Media Over LAN	Yes
KVM Over LAN	Yes
RedFish	Yes
Memory	
Memory Type	DDR5-6400 MT/s (EPYC 9005), DDR5-4800 MT/s (EPYC 9004)
Memory Capacity	Up to 6TB DDR5-6400 MT/s (24 DIMMs)
Storage System	
Hard Drive Bays	SATA/U.2 NVMe (2.5") 8 Hot-Swappable Bays
	M.2 (2280/22110) 2 PCle Gen3
Networking	
Ethernet Controller	Intel® X710-AT2
On-Board LAN	2x 10GbE/RJ45
PCI Expansion Slots	
Number of Slots/Gen/Speed (Size)	8x PCIe Gen5 x16 LP Slots, 4x PCIe Gen5 x16 FHHL Slots
GPU	
GPU Capable	Yes, Up to 8x NVIDIA SXM5
GPU Supported	NVIDIA HGX™ H2OO
External I/O Interfaces	
USB Ports	2x USB 3.2 Gen1
Video Output	1x VGA
Supported Operating System	
Supported OS	RHEL, Rocky
Power System	
Power Supply Size	6x 3000W 80Plus Titanium

Regulatory Compliance	
Regulations	CE, FCC
Mounting Hardware	
Rackmount Rails	Standard Rails included
Operating Environment	
Operating Temperature	10C to 35C (50F to 95F)
Non-operating Temperature	OC to 60C (32F to 140F)
Operating Relative Humidity	8% to 80% (non-condensing)
Non-operating Relative Humidity	20% to 95% (non-condensing)
System Dimensions	
Height	8.75 inches
Width	17.60 inches
Depth	37.20 inches
Warranty	
Warranty	1 Year Standard; For details see the MPSA
Cooling Options	
Air Cooling	Standard
Direct-To-Liquid Cooling	Optional



### **Contact Us**

For sales queries, please contact <u>sales@penguinsolutions.com</u>.

To learn more about the Altus XE5318GTSv2 and other Penguin Solutions products, please visit:  $\underline{www.penguinsolutions.com}$ 

© 2025 Penguin Solutions, Inc. All rights reserved. Penguin Solutions, Penguin Computing, OriginAl, and ICE ClusterWare are trademarks or registered trademarks of Penguin Solutions. All other product names, trademarks, and registered trademarks are the property of their respective owners. All company, product, and service names used in this document are for identification purposes only. Use of these names, trademarks, and brands does not imply endorsement.