PROWOOD"

TrueFrame™ Joist Spans

TRUEFRAME JOISTS-BUILT FOR PROS

The no-nonsense choice for pros who demand precision.



PROWOOD XP

ProWoodXP features MCA preservative with a proprietary additive designed to deliver greater stability—keeping boards straighter for longer.



REDWOOD TONE

Color-infused with redwood-tone colorant for lasting good looks.



KDAT

Kiln-dried after treatment, making boards lighter, easier to transport, handle, and cut, saving contractors time on the job.



UC4A

Treated to meet UC4A Ground Contact standards, ensuring unmatched durability and long-term performance where it matters most.



BACKED FOR LIFE

ProWood Lumber is backed with an industry-leading lifetime limited warranty.

Dry Use - 40 PSF Live Load + 10 PSF Dead Load

Minimum Code (L/360)

	#2 Grade SYP Max Span			TrueFrame Joist Max Span		
Nominal	Actual	12" OC	16" OC	Actual	12" OC	16" OC
2x8	1½" x 7¼"	13'-5"	11'-9"	1½" x 7"	13'-6"	12'-4"
2x10	1½" x 9¼"	16'-2"	14'-0"	1½" x 9"	17'-5"	15'-7"
2x12	1½" x 11¼"	19'-0"	16'-6"	1½" x 11"	21'-3"	18'-7"

Increased Performance (L/480)

	#2 Grade SYP			TrueFrame Joist		
Nominal	Actual	12" OC	16" OC	Actual	12" OC	16" OC
2x8	1½" x 7¼"	12'-2"	11'-1"	1½" x 7"	12'-4"	11'-2"
2x10	1½" x 9¼"	15'-7"	14'-0"	1½" x 9"	15'-10"	14'-4"
2x12	1½" x 11¼"	18'-11"	16'-6"	1½" x 11"	19'-4"	17'-7"

Wet Use - 40 PSF Live Load + 10 PSF Dead Load

Minimum Code (L/360)

	#2 Grade SYP			TrueFrame Joist		
Nominal	Actual	12" OC	16" OC	Actual	12" OC	16" OC
2x8	1½" x 7¼"	13'-1"	11'-9"	1½" x 7"	13'-1"	11'-10"
2x10	1½" x 9¼"	16'-2"	14'-0"	1½" x 9"	16'-10"	14'-5"
2x12	1½" x 11¼"	19'-1"	16'-6"	1½" x 11"	20'-7"	17'-2"

Increased Performance (L/480)

	#2 Grade SYP			TrueFrame Joist		
Nominal	Actual	12" OC	16" OC	Actual	12" OC	16" OC
2x8	1½" x 7¼"	11'-9"	10'-8"	1½" x 7"	11'-10"	10'-9"
2x10	1½" x 9¼"	15'-0"	13'-8"	1½" x 9"	15'-3"	13′-10″
2x12	1½" x 11¼"	18'-3"	16'-6"	1½" x 11"	18'-8"	16'-11"



