



LIFT 1420B

Lift

K	Height to top of working platform in transport position	3990 mm
L	Height to top of arm in folded down position	3620 mm
M	Height to top of arm in transport position	3840 mm
N	Working height	14.2 m
O	Lift angle	76°

LIFT 2000B

Lift

K	Height to top of working platform in transport position	4070 mm
L	Height to top of arm in folded down position	3870 mm
M	Height to top of arm in transport position	4000 mm
N	Working height	20.1 m
O	Lift angle	76°

LIFT 2200C

Lift

K	Height to top of working platform in transport position	3950 mm
L	Height to top of arm in folded down position	3600 mm
M	Height to top of arm in transport position	3840 mm
N	Working height	21.5 m
O	Lift angle	76°



LIFT 1420B

Optimal for railroad work

LIFT 1420B gives you more work opportunities with your machine. It is particularly suitable for railroad work because you can work further away from the machine due to its low weight. Its low transport height also enables passage through most tunnels. The lift can be operated from the cab or the working platform and is designed for two persons or a total weight of up to 200 kg (440 lbs). Stepless leveling provides an excellent working platform at height.

Benefits

- Certified according to the EN 280 standard, which specifies the latest design and safety requirements for mobile elevating work platforms.
- Complies with ISO 13849, safety-related parts of a control system.
- Smooth operation via 4-axis joystick in the cab.
- Durable and well-proven controls on the working platform.
- Stepless leveling provides improved working platform comfort.

Dimensions

Max. work height manual extension	14.2 m
Max. horizontal reach	approx. 10.6 m
Number of hydraulic extensions	3
Slewing angle	355.5°
Slewing torque	5.8 kNm
Attachment coupling	Quick coupling for working platform and pole grab

Weight

Weight	830 kg
Max. load on working platform (irrespective of height)	2 persons + equipment or max. load 200 kg



LIFT 2000B

Built for versatility

LIFT 2000B is very popular for both railroad and overhead line work thanks to its agility and high working height. It is designed for two persons or a total weight of up to 200 kg (440 lbs) and can be operated from the cab or working platform. Stepless platform leveling provides an excellent working platform at height. This is the most popular lift we manufacture thanks to its versatility. This lift is ideal for those who perform a lot of service work.

Benefits

- Certified according to the EN 280 standard, which specifies the latest design and safety requirements for mobile elevating work platforms.
- Complies with ISO 13849, safety-related parts of a control system.
- Smooth operation via 4-axis joystick in the cab.
- Durable and well-proven controls on the working platform.
- Stepless leveling provides improved working platform comfort.

Dimensions

Max. work height manual extension	20.1 m
Max. work height, hydraulic extension	18.1 m
Max. horizontal reach 80 kg load in working platform	approx. 13.5 m
Max. horizontal reach 200 kg load in working platform	approx. 11 m
Number of hydraulic extensions	5
Number of manual extensions	1
Slewing angle	355.5°
Slewing torque	7.5 kNm
Attachment coupling	Quick coupling for working platform and pole grab

Weight

Weight	1250 kg
Max. load on working platform (irrespective of height)	2 persons + equipment or max. load 200 kg



LIFT 2200c

Prepared For LWI

The LIFT 2200C is developed based on customer needs and features several advanced capabilities. It is equipped with a proprietary boom system, a working height of 21.5 meters (70 ft), and increased lifting capacity. The LIFT 2200C is also available in an LWI (Live-Line Work Insulator) version for energized line work. Designed for challenging environments, it allows operators to safely access difficult terrain and perform maintenance and repair work on high-voltage power lines.

Benefits

- LWI version for energized work according to AMS, using the pole method
- Smart Radio Control – no wiring in the work platform, a key requirement for AMS operations
- Adjustable slide blocks on the extension provide a more stable boom system with reduced play
- Increased lifting capacity – 25% stronger than previous models
- Upgraded hydraulics for greater boom reach and smoother operation
- Stepless leveling of the work platform
- Improved platform attachment for reduced play and increased stability
- Enhanced slew bearing delivering up to 100% greater slewing force (encapsulated roller bearing)

Dimensions

Max work height, manual extension or live work kit	21.5 m
Max work height, hydraulic extension	19.5 m
Max horizontal reach with 80 kg load in working platform	approx 15 m
Max horizontal reach with 200 kg load in working platform	approx 12.5 m
Number of hydraulic extensions	6
Number of manual extensions	1
Slew radius	360°
Slewing torque	15 kNm
Control system	Radio control
Attachment coupling	Quick coupler for working platform and pole grab

Weight

Weight	1850 kg
Max load in working platform (regardless of work height)	2 persons + equipment or max. load 200 kg

