

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION

OFFICE OF THE STATE FIRE MARSHAL FIRE ENGINEERING & INVESTIGATIONS DIVISION BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No.:	8140-2084:0004	
PARENT LISTING No.:	: 8140-2041:0004	
CATEGORY:	8140 - EXTERIOR WALL SIDING AND SHEATHING FOR WILDLAND URBAN INTERFACE (W.U.I)	
LISTEE:	WESTERN WOODS INC. P.O. Box 4402, Chico, CA, 95973 Contact: Yale, LInda (530) 343-5821 (530) 343-3851 Email: linday@westernwoodsinc.com	
DESIGN:	Solid-sawn "Wood" siding with no through holes or loose knots, installed over structural plywood or oriented strand board (OSB) with a 7/16" minimum thickness and complying with Voluntary Product Standard PS1 or Voluntary Product Standard PS2, with the following interlocking designs when installed in accordance with industrial technical guide. Refer to the manufacturer's installation instructions and product data sheets.	
	Rabbeted Bevel: When applied in a horizontal orientation with minimum nominal 6" wide and nominal 1" thick boards made of a wood species "Redwood", "Western Red Cedar", "Incense Cedar", "Port Orford Cedar", "Alaska Yellow Cedar", or any other wood species having a Flame Spread Rating not greater than 75 (Class B) when tested in accordance with ASTM E84.	
	All nominal board sizes shall comply with the applicable provisions of American Softwood Lumber Standard DOC PS 20. Edge and end glued siding is permitted to be used interchangeably with solid sawn members. The recommended installation practice for solid wood siding in wall construction regarding butt and overlapping joints is: butt joints between pieces should be staggered a minimum of 12" and all butt joints should be flush with no gap. Nail joints into the studs or blocking members. One nail at each crossing with the wood frame support member shall be used for nominal 6" siding and 2 nails for nominal 8" or wider siding. Refer to the manufacturer's installation instructions and product data sheets.	
RATING:	Compliance with Chapter 7A of the California Building Code.	
INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.	
MARKING:	Listee name. Model number, rating and SFM label.	
APPROVAL:	Listed as solid wood sidings for use in the Wildland Urban Interface areas.	



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION

OFFICE OF THE STATE FIRE MARSHAL FIRE ENGINEERING & INVESTIGATIONS DIVISION **BUILDING MATERIALS LISTING PROGRAM**

NOTES:		
		11-23-11bh
resultsand/ endorseme	or other data but does not make an inder ent or recommendation of the item listed. hts or installation criteria.Refer to listee's c	by the applicant. OSFM Fire Engineering staff has reviewed the test bendent verification of any claims. This listing is not an This listing should not be used to verify correct operational lata sheet, installation instructions and/or other suitable
te Issued: 06/12/202	5	Listing Expires: 06/30/202
	Huang , Program Coordinator ering & Investigations Division	