

## UHF | RAIN - Hard Tags Xerafy - TEX TRAK

- Available with NXP U-Code chips
- Over 200 washing cycles
- Up to 10 meter reading range
- Apply by sewing or heat seal
- Can be personalized



### UHF | RAIN - Laundry Perfect for industrial Laundry

The Xerafy TEX TRAK series of washable RFID tags helps redefine how healthcare and hospitality manage textile inventory, offering unparalleled efficiency and control. Engineered for industries where hygiene and inventory control are paramount, the RFID laundry tags cater to industrial laundries, hotels, hospitals, brands, and beyond. The high-performance RFID tags address common challenges in volume laundry tracking, ensuring a seamless process and delivering superior benefits.

Traditional laundry tracking methods often lead to errors, misplaced items, and low productivity. Say goodbye to manual tracking and hello to automated precision. With the Xerafy series of RFID laundry tags, experience streamlined processes, accurate inventory management, and enhanced security in your laundry operations.

The TEX TRAK series can be combined with similar durable hard tags to cover a wider range of assets.

#### Common Applications

- First choice for industrial laundry
- Best for hospitals
- Best for hotels
- Best for wellness & spa



TEX 70x15

TEX 50x12

TEX 55x12 Silicone



OEM Part Number (P/N)	X7015-GL010-U8 (Global, Sew) X7015-GL011-U8 (Global, Heat-seal)	X5012-GL010-U8 (Global, Sew) X5012-GL011-U8 (Global, Heat-seal)	X5512-GL070-U9 (Global)
Frequency	860-960 MHz (Global)	860-960 MHz (Global)	860-960 MHz (Global)
IC type	NXP UCODE 8	NXP UCODE 8	NXP UCODE 9
Chip memory	96 bits TID / 128 bits EPC	96 bits TID / 128 bits EPC	96 bits TID / 96 bits EPC
Read range on metal (fixed)	Limited	Limited	Up to 10 m
Read range off metal (fixed)	Up to 12 m	Up to 6.50 m	Limited
Material	Textile	Textile	Silicone
Mounting systems	Sew or heat-seal based on specific requirements, with different product P/N selections	Sew or heat-seal based on specific requirements, with different product P/N selections	Sew
Operational temperature	-20°C to +85°C	-20°C to +85°C	-40°C to +85°C
Survival temperature	-40°C to +110°C	-40°C to +110°C	-40°C to +85°C
Compression strength	245 kPa	245 kPa	490 kPa
IP rating	IP68	IP68	IP68
Dimensions	70 x 15 x 0.85 mm	50 x 12 x 0.85 mm	55 x 12 x 2.50 mm
Weight	1000pcs/bag / 0.43 kg	1000pcs/bag / 0.15 kg	1.99 g
Applications	Medical scrubs Hospital linens Hotel linens Uniforms Rental costumes	Medical scrubs Hospital linens Hotel linens Uniforms Rental costumes	Medical scrubs Hospital linens Hotel linens Uniforms Rental costumes