What is a Universal Pulling Tool?

This Universal Pulling Tool is used for the retrieval or release of downhole components. Its adaptability to different operations without the need for separate tools or additional parts is its primary feature. This tool is designed for smooth transition between shear-up to release (compatible with Camco type 'JU' or Os type 'R' tool) and shear-down to release (compatible with Camco type 'JU' or Os 'S' tool). It achieves this versatility through its innovative design, eliminating the need for operators to switch between multiple tools for different tasks.

Applications

- Used to retrieve tools by latching to an external fishneck.
- Combines both a shear-down and shear-up pulling tool into one tool.

Key Features & Benefits

- Equipped with an adjustable core, allowing it to retrieve components with external fish necks of varying lengths or reach.
- Can be re-pinned without disassembling the tool.
- 1.50", 2.00", 2.5", 3.00", 4.0" tools available for either standard or H²S service.



| Technical Data | | | | | | | | |
|--|------------------|------------------|------------------|------------------|------------------|--|--|--|
| Nominal Size | 1.500" | 2.000" | 2.500" | 3.000" | 4.000" | | | |
| Assembly Number | 03-01-UPT-150-A0 | 03-01-UPT-200-A0 | 03-01-UPT-250-A0 | 03-01-UPT-300-A0 | 03-01-UPT-400-A0 | | | |
| Actual O.D. | 1.430" | 1.860" | 2.250" | 2.800" | 3.750" | | | |
| Tool Fish Neck Size | 1.187" | 1.375" | 1.375" | 1.750" | 2.312" | | | |
| Tool Connection | 0.94" - 10 UN | 0.94" - 10 UN | 0.94" - 10 UN | 1.063" - 10 UN | 1.562"-10 UN | | | |
| Fishneck Size Engaged | 1.187" | 1.375" | 1.750" | 2.313" | 3.125" | | | |
| Reach | Short | | | | | | | |
| | 1.30" | 1.25" | 1.30" | 1.38" | 1.74" | | | |
| | Medium | | | | | | | |
| | N/A | 2.05" | 2.10" | 2.20" | 2.44" | | | |
| | Long | | | | | | | |
| | 1.95″ | 2.60" | 2.60" | 2.70" | 3.14" | | | |
| Approximate Weight | 2 KG | 5 KG | 6 KG | 9 KG | 11 kg | | | |
| Working Strength (110 KSI Material) | 18,000 lbs | 25,000 lbs | 36,000 lbs | 50,000 lbs | 62,000 lbs | | | |

See next page for parts list.

| Parts List | | | | | | | | |
|-----------------------------|---------------------|---------------------|---------------------|--------------------|--------------------|--|--|--|
| Nominal Size | 1.50" | 2.00" | 2.50" | 3.00" | 4.00" | | | |
| Assembly Number | 03-01-UPT-150-A0 | 03-01-UPT-200-A0 | 03-01-UPT-250-A0 | 03-01-UPT-300-A0 | 03-01-UPT-400-A0 | | | |
| Part Name | Part Number | | | | | | | |
| Fishneck | 03-01-UPT-150-01 | 03-01-UPT-200-01 | 03-01-UPT-250-01 | 03-01-UPT-300-01 | 03-01-UPT-400-01 | | | |
| Retainer Segments | 03-01-UPT-150-02 | 03-01-UPT-200-02 | N/A | N/A | N/A | | | |
| Upper Cylinder | 03-01-UPT-150-03 | 03-01-UPT-200-03 | 03-01-UPT-250-03 | 03-01-UPT-300-03 | 03-01-UPT-400-03 | | | |
| Spring Retainer Lock Nut | N/A | 03-01-UPT-200-05 | 03-01-UPT-250-05 | 03-01-UPT-300-05 | 03-01-UPT-300-05 | | | |
| Spring Retainer Nut | 03-01-UPT-150-05 | 03-01-UPT-200-06 | 03-01-UPT-250-06 | 03-01-UPT-300-06 | 03-01-UPT-300-06 | | | |
| 2 or 3 Position Core | 03-01-UPT-150-07 | 03-01-UPT-200-07 | 03-01-UPT-250-07 | 03-01-UPT-300-07 | 03-01-UPT-400-07 | | | |
| Shear Pin Retainer | 03-01-UPT-150-08 | 03-01-UPT-200-08 | 03-01-UPT-250-08 | 03-01-UPT-300-08 | 03-01-UPT-400-08 | | | |
| Dog | 03-01-UPT-150-09 | 03-01-UPT-200-09 | 03-01-UPT-250-09 | 03-01-UPT-300-09 | 03-01-UPT-400-09 | | | |
| Dog Spring Washer | 03-01-UPT-150-11 | 03-01-UPT-200-11 | 03-01-UPT-250-11 | 03-01-UPT-300-11 | 03-01-UPT-400-11 | | | |
| Pawls | 03-01-UPT-150-12 | 03-01-UPT-200-12 | 03-01-UPT-250-12 | 03-01-UPT-300-12 | 03-01-UPT-400-12 | | | |
| Lower Cylinder (Skirt) | 03-01-UPT-150-13 | 03-01-UPT-200-13 | 03-01-UPT-250-13 | 03-01-UPT-300-13 | 03-01-UPT-400-13 | | | |
| Core Spring | 03-01-UPT-150-14 | 03-01-UPT-200-14 | 03-01-UPT-250-14 | 03-01-UPT-300-14 | 03-01-UPT-300-14 | | | |
| Dog Spring | 03-01-UPT-150-15 | 03-01-UPT-200-15 | 03-02-GS-200-07 | 03-01-UPT-300-15 | 03-01-UPT-300-15 | | | |
| Set Screw | 1/4" UNF x 3/16" LG | 5/16" UNC x 1/4" LG | 5/16" UNC x 1/4" LG | 3/8" UNC x 1/4" LG | 3/8" UNC x 3/8" LG | | | |
| Shear Pin | 3/16" x 1" LG | 5/16" x 1-1/2" LG | 5/16" x 1-3/4" LG | 3/8" x 2.35" LG | 3/8" x 2.78" LG | | | |

Speak with a Brace Tool sales representative to explore the different configurations available on this tool and discover how we can match your requirements.