

# Color Filter Wheel

## CFW9-5

### Precision Machined Reliable Performance

FLI color filter wheels are engineered for reliable performance, ideal for harsh or remote environments. Each wheel features a proprietary no-slip drive chain, a precision stepper motor, and a large-diameter pivot pin paired with precision-ground bushings—delivering smooth, quiet, and dependable operation. And because FLI filter wheels do not use internal lights for homing, your images remain fully protected from stray light interference.

The CFW9-5 supports unmounted filters, 1 mm to 5 mm thick.



#### Technical Data

<b>Filter Positions</b>	5
<b>Recommended Filter Size (+/- 0.125 mm)</b>	65mm Square
<b>Filter Thickness Range</b>	1 to 5 mm
<b>Wheels</b>	1
<b>Overall Thickness (less motor)</b>	0.595" (15.11 mm)
<b>Weight</b>	3.2 lbs. (1.45 kg)
<b>Interface</b>	USB
<b>Camera Side Connection</b>	10-32 Bolt Pattern
<b>Optical Side Connection</b>	M92-1 thread
<b>Wheel Material</b>	Aluminum
<b>Power</b>	12V
<b>Drawing</b>	See Accessories page of FLI website



\* MADE IN USA \*



Finger Lakes Instrumentation  
FLIcamera.com  
USA 585-624-3760