FINGER LAKES INSTRUMENTATION

AURORA CMOS CAMERA

AR455.

DATASHEET flicamera.com/models/ar455

MADE IN USA

PRODUCT PAGE

61.2 Megapixels at Up to 4 fps

Made in USA with the same extreme reliability FLI's OEM customers rely on. Install in remote observatories around the world with complete confidence in a long, trouble-free life. Full frame sensor with 91% quantum efficiency and massive 43.2 mm diagonal field of view to increase throughput.



Aurora with FLI Dovetail Flange

KEY SPECIFICATIONS

SENSOR	SIZE (MM)	RESOLUTION	PIXEL SIZE
Sony IMX455	36 X 24 mm (43.2 mm)	9568 x 6380	3.76 x 3.76 µm

FULL WELL	READ NOISE	DARK CURRENT	PEAK Q.E.
50000 electrons	1 e- (rolling)	0.002 eps at -20C	91%

TECHNICAL DATA


Sensor Type	Back Illuminated CMOS
Shutter Type	Rolling; Rolling with Global Reset
Pixel Size (microns)	3.76 x 3.76 µm
Full Well Capacity (e-)	50000 electrons
Dynamic Range	93.6 dB
Cooling Method	Air or optional Liquid [1]
Temperature Stability	0.1°C
Interface	USB 3.0
Optional Shutter	None
Subarray Readout	Yes
SDK / Software	LIBFLI / FLIGrab

Sensor	Sony IMX455
Active Pixels	9568 x 6380
Imaging Area (Diagonal)	36 X 24 mm (43.2 mm)
Typical Readout Noise	1 e- (rolling)
Frame Rate (fps)	4 fps
Max. Cooling (Air)	50°C below ambient
Dark Current (typical)	0.002 eps at -20C
Data Bit Depth	12 / 16 bit
Optional Mounts	Nikon F-Mount
External Trigger In/Out	Yes
Weight	2 lbs (.9 kg)


Peak QE	91%

TECHNICAL FIGURES

Absolute quantum efficiency



Mechanical outline



NOTES AND OPERATING CONDITIONS

1 Cameras are plumbed for liquid circulation; External liquid circulation connectors sold separately.

See FLIcamera.com for alternate configurations

FINGER LAKES INSTRUMENTATION · MADE IN USA

Request a quote for AR455

REQUEST A QUOTE

flicamera.com/models/ar455 · USA 585-624-3760