How to Replace a Roof: DIY Checklist

Evaluate Whether You Need a New Roof

	Roof is 20–25+ years old	
	Shingles missing, cracked, or bald	
	Water stains or sagging in attic	
	Storm damage: lifted flashing or hail dents	
	Frequent leaks or rusted fasteners	
Re	view Safety and Risk Factors	
	Wear harness, roof jacks, and safety ropes Set up ladder safely with 3-point contact Avoid work in bad weather or slick surfaces Acknowledge physical strain and stay alert Have emergency plan and don't work alone	
Gather Essential Tools & Materials		
	Roofing shingles or metal roofing Underlayment Ice & water shield Roof vents, ridge cap shingles, flashing Roofing paper, roofing nails, roofing cement Roofing shovel to remove old shingles Pry bar, utility knife with hook blades Nail gun + compressor, circular saw, tin snips Chalk line, safety harness, magnetic nail sweeper	
Step 1: Obtain Roofing Permits		
	Check local permit rules Submit application and get approval Schedule required inspections Review HOA restrictions (if any)	

Step 2: Preparation and Safety Setup

	Pick 2–4 dry days Set up safety gear and roof jacks Tarp landscaping and walkways Rent or prep a dumpster Inform nearby neighbors	
Step 3: Tear-Off and Deck Inspection		
	Strip shingles, nails, and underlayment Check decking for rot or damage Replace soft or sagging sheathing Re-nail loose panels	
Step 4: Install Underlayment and Flashing		
0	Add ice/water shield in key areas Install underlayment with proper overlap Place drip edge at eaves and rakes Flash chimneys, vents, and valleys	
Step 5: Shingle Installation and Ventilation		
	Lay starter strip on eaves and rakes Nail shingles in staggered rows Cut vents as needed Check attic airflow alignment	
Step 6: Ridge Cap and Final Sealing		
	Install ridge vent and cap shingles Check nails, flashing, and alignment Clear roof and gutters Sweep yard for stray nails	

