

AI-READY

40-Series Dual Sliding Door



The Only Door Designed for the Demands of High Pressure, High kW, AI Environments

ScaleWRX 40-Series Dual Sliding Doors are built using the highest quality materials and components ensuring they can handle the unique demands of HPC and AI environments. Our doors are expertly engineered to withstand higher air pressures and the rigorous demands of daily use while still delivering the high-end, elegant design and durability that define ScaleWRX products. All of our products are manufactured in the United States, enabling expedited lead times to meet even the most demanding project schedules.

KEY FEATURES



Highest Industry Durability



Components are 1,000,000 Cycle Count



No Routine Maintenance Required For Closer Assembly




Shatter-Proof Inserts



Mechanically Fastened Valance





40-Series Dual Sliding Door Product Specifications

Framework

Material	Profile	Tensile Strength, PSI
Aluminum	40-Series	35,000
Max. Frame Size	Width	Height
	105 inches	101.25 inches
Max. Oversize Width		
	180 inches	
Min. Door Size	Width	Height
	80 inches	80 inches
Effective Opening	Width	Height
	Up to 46 inches	96 inches
Door Depth	With Handle	Without Handle
	Less than 6 inches	Less than 4 inches

Inserts

Material	Flame Rating and Smoke Rating
3MM / .125" Solid Polycarbonate	Flame Spread Index: 5 Smoke Developed Index: 250
8MM Multiwall	Flame Spread Index: 5 Smoke Developed Index: 300

STANDARD FEATURES

- Custom Sized (to 1/8")
- Rigid Design
- No Threshold
- Auto-Closing
- Soft-Closing
- Hold Open
- Modular Design
- Clear or Black Anodized Finish

CUSTOMIZABLE OPTIONS

- Custom Designs and Logos
Vinyl or Etched
- Bi-Part Feature
- Inserts

