

30-Series Hinged Door

Engineered for Precision. Built for Performance.

ScaleWRX 30-Series Hinged Door delivers the perfect balance of durability, precision, and performance for today's data center environments. Built with the same high-quality craftsmanship that defines every ScaleWRX product, the 30-Series is engineered to provide a reliable containment solution that maintains efficiency, safety, and uptime in both hot and cold aisle applications. Its combination of high-quality components, clean design, and dependable performance make it an ideal solution for facilities that require lasting containment without compromise.

KEY FEATURES



High Quality Components



No Routine Maintenance Required For Closer Assembly



Shatter-Proof Inserts



Self Closing With Damper & Hold-Open





30-Series Hinged Door Product Specifications

Framework

Material	Profile	Tensile Strength, PSI
Aluminum	30-Series	35,000
Max. Frame Size	Width	Height
	55 inches	105 inches
Min. Door Size	Width	Height
	24 inches	80 inches
Effective Opening	Width	Height
	Up to 47 inches	Up to 100 inches
Door Depth	With Handle	Without Handle
	Less than 3.5 inches	Less than 1.25 inches

Inserts

Material	Flame Rating and Smoke Rating
3MM / .125" Solid Polycarbonate	Flame Spread Index: 5 Smoke Developed Index: 250
8MM Multiwall	Flame Spread Index: 5 Smoke Developed Index: 300



STANDARD FEATURES

- Custom Sized (to 1/8")
- Rigid Design
- No Threshold
- Auto-Closing
- Soft-Closing
- Hold Open
- Modular Design
- Clear Anodized Finish
- Left or Right Swing

CUSTOMIZABLE OPTIONS

- Custom Designs and Logos Vinyl or Etched
- Inserts

