


TREAD PLATE

ALLOY 5052: TREAD PLATE 5 BAR



EX STOCK	THICKNESS MM	WIDTH MM	LENGTH MM	ALLOY TYPE	TEMPER	KILO/SHEET
	T	W	L			
✓	1.6	1200	2400	5052	H114#	12.85
✓	2.0	1200	2400	5052	O	16.16
✓	3.0	1200	2400	5052	H114#	24.01
✓	3.0	1200	4800	5052	H114#	48.59
✓	3.0	1500	3600	5052	H114#	45.44
✓	3.0	1500	4500	5052	H114#	56.46
✓	3.0	1700	4000	5052	H114#	58.03
✓	4.0	1200	2400	5052	H114#	32.46
*	4.0	1200	4800	5052	H114#	69.88
✓	4.0	1500	3600	5052	O	59.15
✓	4.0	1500	4500	5052	O	74.72
✓	5.0	1200	2400	5052	H114#	39.43
✓	5.0	1500	3000	5052	O	61.79
*	5.0	1500	3600	5052	O	72.34
✓	6.0	1200	2400	5052	O	48.09
✓	6.0	1500	3000	5052	O	73.73
*	6.0	1500	3600	5052	O	91.30

Base Thickness = As Above. Approx Total Thickness = Add 1.0-1.5mm

BRIGHT PROPELLER PATTERN: ONE BAR TREAD PLATE PROPELLER

EX STOCK	THICKNESS MM	WIDTH MM	LENGTH MM	ALLOY TYPE	TEMPER	KILO/SHEET
	T	W	L			
✓	1.6	1200	2400	3003	H22	13.40
✓	3.0	1200	2400	3003	H22	24.94

W = Width L = Length T = Thickness

All sheet is mill finish unless otherwise stated

* Please ask regarding the ex stock availability

Indent available for alternative sizes and thickness

All weights shown are theoretical and the actual weight may vary

Temper may also be O or F