



TEE/I BEAM/TOP HAT

ALLOY 6060: 5 METRE LENGTHS




SECTION	EX STOCK	SIZE MM			KILO / METRE	PERIMETER MM
		A	B	T		
90043	*	25.0	25.0	1.6	0.209	100
60031	✓	25.0	25.0	3.0	0.382	100
31000	✓	40.0	40.0	3.0	0.626	159.7
31102	✓	40.0	50.0	6.0	1.366	179.2
90096	*	44.4	25.4	2.5	0.456	136
60207	*	50.0	22.0	3.0	0.561	143.4
90104	✓	50.0	50.0	3.0	0.789	200
60188	✓	50.0	50.0	6.0	1.528	199.2
60211	✓	50.0	75.0	6.0	1.977	244.1
60170	✓	50.0	100.0	6.0	2.341	299.2
60080	*	50.0	150.0	8.0	4.162	399.2
60072	*	65.0	65.0	6.0	2.016	259.2
60181	*	75.0	125.0	10.0	5.149	399.2
90016	*	100.0	65.0	5.0	2.168	330
60003	*	100.0	80.0	5.0/7.0	2.777	359.2
60210	*	100.0	90.0	10.0	4.878	379.2

I BEAM: ALLOY 6060



SECTION	EX STOCK	SIZE MM			RADIUS	KILO / METRE	PERIMETER MM
		A	B	T			
60197	*	90.0	108.0	3.000	-	2.379	558.6

TOP HAT: ALLOY 6060



SECTION	EX STOCK	SIZE MM				RADIUS	KILO / METRE	PERIMETER MM
		A	B	C	T			
60014	*	38.0	18.0	15.0	1.5	FULL ON LEGS	0.285	142.0
60127	*	140.0	35.0	57.0	2.0/2.5/3.2	0.80/5.0	1.270	366.7

A = Width B = Height T = Thickness R = External Radii

* Mill runs only, please ask regarding the availability of these

Other stock lengths available in this size. If the product you require is not listed please enquire