

T(P)GS-H7508XTR

8 GT + 5 10G Copper M12 Push-Pull X-coded (PoE) EN50155
Managed Ethernet Security Switch w/optional L3L/L3 &
Cybersecurity, WVI input



OVERVIEW

Lantech T(P)GS-H7508XTR is a high-performance OS5 managed ethernet security switch with 8 10/100/1000T + 5 100M/1G/2.5G/5G/10G Copper PoE switch (total 13 ports) w/ M12 X-coded Push-Pull connectors. The OS5 platform supports L3/L2, IPv6/v4, NAT**, standardized ITU G.803 ring, IEC62443-4-2 certified cybersecurity, SNMPv3, Macsec**, PTP v2** as well as ETBN TTDP** protocol suitable for the future-proof modern network.

Lantech OS5 platform is equipped with complete L2 management and L3 communication protocols incl. dynamic routing, multicast routing, hardware NAT and ETBN TTDP; optional PTP, MacSec to be upgradable

The switch runs on the Lantech OS5 platform which is powerful with complete Layer 2 management features and major L3 protocols inclusive of RIP, OSPF, PIM, DVMRP, IEC61375-2-5 (ETBN), and hardware-based NAT. It also supports optional Macsec for authentication and encryption between two Macsec devices. The optional PTP V2 and gPTP support transparent clock, boundary clock and ordinary clocks with 2-step processing that synchronizes network time accuracy to sub-microseconds. To learn more about the Lantech OS5 Platform, please refer to [Lantech OS5 Software Datasheet](#)

Certified cybersecurity development process with IEC 62443-4-1, and IEC 62443-4-2* certificate with physical tamper resistance and detection for integrity and authenticity of the boot process

Lantech OS5 platform is designed with a high standard of cybersecurity to prevent threats from network attacks. To ensure the safety and reliability of communication networks, Lantech software development is certified with IEC 62443-4-1 security process standards and the switch is also certified with IEC 62443-4-2*. The switch uses roots of trust to verify the integrity and authenticity of the firmware, software, and configuration data needed for the switch's boot process.

To learn more about Lantech cybersecurity software solutions, please refer to [Lantech OS5 Software Datasheet](#)

SNMP v3 Security Models

SNMPv3 enhances security with three key models. The User-based Security Model (USM) provides authentication and encryption, verifying the sender's identity and protecting data. The View-based Access Control Model (VACM)

manages user access to specific objects based on their security level. The Transport Security Model (TSM) uses secure protocols like TLS or DTLS for communication encryption. Together, these models make SNMPv3 implementations highly secure, meeting modern cybersecurity standards for large-scale and high-security projects.

Comprehensive Network Protection Against DDoS and Layer 2 Threats

Lantech OS5 generation integrates advanced security mechanisms to safeguard both switches and networks. Key features include DDoS attack mitigation, 802.1X port-based authentication, Dynamic ARP Inspection (DAI), IP Source Guard, and Port Security, providing multi-layer protection against spoofing, unauthorized access, and traffic floods. These security capabilities ensure stable, resilient network operation.

Support Restful API for better switch performance; Auto-provisioning* for firmware/configuration update

The switch supports Restful API that uses JSON format to access and use data for GET, PUT, POST and DELETE types to avoid traditional SNMP management occupying CPU utilization. The OPEN API document format for Restful API can greatly improve central management efficiency for various applications including fleet management and AIOT.

It also supports auto-provisioning for switch to auto-check the latest software image and configuration through TFTP server.

Optional IEC 61375-2-5/3-4 ETBN/ECN TTDP protocol, RNAT and proprietary DHCP and VLAN over TTDP

Lantech optional L3L/L3 license includes IEC 61375-2-5 and 3-4 ETBN standardized TTDP protocol that automatically assigns the switch IP address reflecting its location to adapt with various train-car arrangements of the operator's plan. With RNAT (railway NAT), each car device's IP address can be routed to the specific server and proprietary DHCP and VLAN over TTDP to help manage fixed IP address per device as well as the segmentation of VLAN in ECN.

Redundant dual WVI power input w/ power transient, inrush current, polarity reverse and over-heat protection

The T(P)GS-H7508XTR WVI model accepts 16.8~137.5VDC dual inputs with galvanic isolation to PoE and all Ethernet ports. The switch incorporates a power protection circuit to safeguard against potential adverse effects and hazards from power transients (surges, spikes, power fluctuations). It is also designed to clamp inrush current and protect from polarity reversal damage. The switch will automatically disable power output when the switch ambient temperature is over 85°C and re-boot when the temperature is back to normal.

Up to 10 PoE ports include 8 IEEE 802.3at/af and 2 T4 PoE 802.3bt/at/af (-10) w/advanced PoE management and PoE galvanic isolation with max PoE budget, support Perpetual/Fast PoE

Compliant with 802.3 bt/at/af standard, the PoE model can feed 24 PoE ports up to 30 Watt@ or 24 PoE 30 Watt@ and 2 PoE IEEE 802.3bt to feed T4 PoE up to 90 Watt@ for various PD devices. The switch supports 120W PoE budget. It supports advanced PoE management including PoE detection and scheduling. PoE detection can detect if the connected PD hangs then restart the PD; PoE scheduling is to allow a pre-set power feeding schedule upon a routine timetable. Each PoE port can be enabled/disabled, get the voltage, current, Watt, and temperature info displayed on WebUI.

Perpetual and Fast PoE provides immediate and continuous power to devices during PSE switch reboots.

The PoE galvanic isolation provides insulation between the power input to PoE Ethernet ports, preventing cabling and grounding incidents from damaging the Ethernet switch. The efficiency of the galvanically decoupled voltage converters can reach above 90%.

Support RTC (Real Time Clock) with longevity golden capacitor

Our switch supports RTC which is powered by a golden capacitor, ensuring accurate real-time event logs for all

times. Unlike traditional batteries, golden capacitors offer superior reliability, and longevity, without a need to change battery.

User-friendly GUI, Auto topology drawing, Enhanced Environmental Monitoring

The user-friendly UI, innovative auto topology drawing, and topology demo make the switch much easier to get hands-on. The complete CLI enables professional engineers to configure settings by command line. It supports enhanced environmental monitoring for actual input voltage, current, switch ambient temperature and total power load.

Event log & message; 2DI + 2DO; Factory default pin

T(P)GS-H7508XTR provides 2DI and 2DO. When disconnection of the specific port was detected; DO will activate the signal LED to alarm. DI can integrate the sensors for events and DO will trigger the outside alarm and switch will send alert information to IP network with email and traps.

The factory reset pin can restore the setting back to factory default.

Editable configuration file; USB port for import/export configuration

The configuration file of the switch can be imported and edited with a word processor for the following switches to configure with ease. The USB data port can import/export the configuration from/to the USB dongle and also to upgrade firmware. It supports USB console port that allows CLI access.

Optional smart bypass protection on dual/quad 10G copper ports

The bypass relay is set to bypass the switch to the next one when power is off to prevent network disruption. Lantech bypass caters to remain in bypass mode until the switch is completely booting up when power is back to avoid another network loss. An optional smart bypass (Up to two pairs) can be activated when switch encounters power failure. (-BT/-BBT model)

EN50155, EN45545-2; EN61373 compliance; IP41 rack mount design

The IP41 aluminum alloy enclosure with M12 connectors for waterproofing. With EN50155 verification along with EN45545-2 Fire & Smoke compliance, this switch is ideally suited for railway on-board/trackside, vehicle, and other rugged applications. The switch operates under wide-ranging temperatures from -40°C to 70°C (-40°F to 158°F) (EN50155 T4).

OS5 vs. OS5 - SEC models comparison

	OS5	OS5 - SEC
IEC 62443-4-2 Cyber Security	NA	Y, need optional license
Boot up time	Around 100 sec.	Around 135 sec.

DIMENSIONS (unit=mm)

SPECIFICATIONS

Hardware Specification

Standards	IEEE802.3 10Base-T Ethernet IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T IEEE802.3an 10Gbase-T IEEE802.3x Flow Control and Back Pressure IEEE802.3ad Port trunk with LACP IEEE802.1d Spanning Tree IEEE802.1w Rapid Spanning Tree IEEE802.1s Multiple Spanning Tree IEEE802.3ad Link Aggregation Control Protocol (LACP) IEEE802.1AB Link Layer Discovery Protocol (LLDP) IEEE802.1X User Authentication (Radius) IEEE802.1p Class of Service IEEE802.1Q VLAN Tag IEEE802.3at/af Power over Ethernet Type 3 IEEE802.3bt Power over Ethernet Type 4 IEEE802.3bt Power over Ethernet
Switch Architecture	Back-plane (Switching Fabric): 116Gbps
Mac Address	32MAC address table
Jumbo frame	10KB
Connectors	10/100/1000T: 8 ports M12 X-coded with Push-Pull connectors 100M/1G/2.5G/5G/10G: 5 ports M12 X-coded with Push-Pull connectors Power Input connector: 1 x M12 5-pole Male K-coded Reset/Console/USB: 1 x M12 8-pole Female A-coded with Push-Pull connectors DIDO: 1 x M12 5-pole Female A-coded with Push-Pull connectors
Network Cable	100Base-TX: 2-pair STP Cat. 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) 1000Base-TX: 2-pair STP Cat. 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) 10G Copper: 4-pair STP Cat6a/7 cable
LED	Per unit: Power 1 (Green), Power 2 (Green), FAULT (Red) 100/1000T Ethernet port: Link/Activity (Green), Speed (Green); R.M. indicator (Green) PoE: Link/Act (Green) 100/1G/2.5G/5G/10G Copper port: Speed (100/1G/2.5G/5G: Yellow; 10G: Orange)
DI/DO	2 Digital Input (DI): Level 0: -30~2V / Level 1: 10~30V Max. input current:8mA

	2 Digital Output (DO): Open collector to 40 VDC, 200mA
Operating Humidity	5% ~ 95% (Non-condensing)
Operating Temperature	-40C~70C / -40F~158F (85°C operation for 10min.)
Storage Temperature	-40°C~85°C / -40°F~185°F
Power Supply	Dual DC input 16.8~137.5VDC
Inrush Current	6A
PoE Budget (PoE model)	120W
PoE pin assignment (PoE model)	M12 port #1~#8 (AT 30W); M12 port #9~#10 (BT 90W) support IEEE 802.3bt/at/af End-point, Alternative A mode
Power Consumption	Max. 65W excludes PoE load
Dimensions	IP41 Aluminum alloy case (rack mount): 440mm(W)x44mm(H)x354mm(D)
Weight	5kgs
Installation	Wall Mount Design
EMI & EMS	FCC Part 15 Class A EN61000-6-2 EN61000-6-4 CE EN55032 Class A CE EN55024 CE EN61000-4-2 (ESD) Level 3 CE EN61000-4-3 (RS) Level 3 CE EN61000-4-4 (EFT) Level 3 CE EN61000-4-5 ED3 (Surge) Level 3 CE EN61000-4-6 (CS) Level 3 CE EN61000-4-8 (Magnetic field) Level 3
Verifications	EN50155/EN50121-3-2/EN50121-4; EN 45545-1, EN 45545-2 Fire & Smoke verification
Stability Testing	EN61373 (Shock and Vibration)
MTBF	226,702hrs (standards: IEC 62380)
Warranty	5 years
Bypass**	Up to two pairs bypass modules on 10GT ports to pass to the next switch in case of power failure and CPU fail
Software Specification	
Lantech OS5 Platform	Download Software Datasheet

*Future release

**Optional

ORDERING INFORMATION

All model packages include M12 caps. For conformal coating add -C to Model Name. For optional bypass add -BT (one pair); -BBT (two pairs). For optional PTP add -PTP; For optional MacSec add -MacSec

- **TPGS-H7508XTR-10-41-WVI.....P/N: 8361-0201**
8 100/1000T PoE at/af + 5 100M/1G/2.5G/5G/10G M12 X-coded w/2 T4 PoE bt EN50155 OS5 Managed Ethernet Switch; 16.8V~137.5V dual input; IP41 rack mount design; -40°C to 70°C; w/PoE & ethernet galvanic isolation
- **TGS-H7508XTR-41-WVI.....P/N: 8361-0202**
8 100/1000T + 5 100M/1G/2.5G/5G/10G M12 X-coded EN50155 OS5 Managed Ethernet Switch; 16.8V~137.5V dual input; IP41 rack mount design; -40°C to 70°C; w/ ethernet galvanic isolation

OPTIONAL ACCESSORIES

Software package

Please refer to the [software datasheet](#)

M12 Connector & Cable

Connector

■ ECONM12-08A(M)-180	8 pin M12 (Male) A-coded 180 degrees crimp type connector for reset/console/USB
■ ECONM12-05A(M)-C-180	5 pin M12 (Male) A-coded 180 degree crimp type connector for DI/DO
■ ECONM12-08X(M)-SPEEDCON	8 pin M12 (Male) X-coded 180 degrees crimp type connector for data, Ethernet CAT6A (10G), shielded, SPEEDCON
■ 4106-0000097-001	5 pin M12 (Female) K-coded 180 degrees screw type connector for power supply
■ ECONM12-05K(F)-S-180	

Cable


■ ECABM12X83MSTP	8 pin M12 (Male) X-coded 180 degrees RJ45 STP cable for data, shielded, 300cm
■ ECONM12-08M2-CONSOLE	8 pin M12 (Male) A-coded 180 degree to RS232 cable for console, 150cm
■ 4106-0000096-001	5 pin M12 (Female) K-coded 90 degrees 1.5M cable for power supply
■ ECABM12-05K(F)-90-1.5M	

Others

■ 4106-0000093-001	8 pin M12 (Male) A-coded 180 degrees to USB Female/male plug, 150cm
--------------------	---

Managed Switch OS Generations

We offer a comprehensive range of managed switches, from OS1 and OS2 with rich L2+ management features, to OS2 PRO with basic routing functionality, and OS3, OS4, and OS5, which can be upgraded with optional Layer 3 Lite or Layer 3 capabilities to meet diverse customer needs. Note: Model differences include both software features and hardware specifications.

**[LEARN MORE]**

- [OS2PRO Generation](#)
- [OS3/OS4 Generation](#)
- [OS5 Generation](#)

[CHECK THE DIFFERENCES]

- [Generation Comparison Table](#)

Lantech Communications Global Inc.

www.lantechcom.tw
info@lantechcom.tw

© 2024 Copyright Lantech Communications Global Inc. All rights reserved. Updated on 21 JAN 2026
The revised authority rights of product specifications belong to Lantech Communications Global Inc.
In a continuing effort to improve and advance technology, product specifications are subject to change without notice.