

T(P)WMR-5006

EN50155 Multifunction VPN Router w/1x WiFi 11ac + 1 LTE 4G + 2 serial ports + 6 Gigabit X-coded Ethernet switch (incl. 4 PoE ports) w/ Load Balancing, VPN, Protocol Gateway, Storage**; WV input



OVERVIEW

Lantech T(P)WMR-5006 series is a next generation EN50155 multi-function VPN router w/ 1 x 802.11ac Wi-Fi + 1 x LTE modem + 6 Gigabit X-coded Ethernet switch incl. 4 PoE ports (PoE model) + 2 serial ports that supports advanced function of VPN, Load-Balancing, EMMC Flash Storage**, Protocol gateway (Modbus), Storage**, Wi-Fi roaming and LTE dual SIM fail-over for industrial applications. The dual core CPU with 1.6GHz + 256M flash enables the router to multi-task smoothly.

LTE design 4G/3G w/2SIMs for redundancy

With one mobile LTE module (1L model), 2 SIM card slots, T(P)WMR-5006 provides redundant link between two service providers. Both GPS and Russian GLONASS systems are supported.

Optional EMMC Flash storage**

The optional EMMC flash storage on the router can offer 8G/16G/32G capacity.

Optional eSIM**

By replacing physical SIM, optional eSIM chip will allow users to purchase data plans at low prices from local carriers in the world.

IEEE 802.11ac one band radio up to 1.3Gbps bandwidth

With IEEE 802.11ac capability, T(P)WMR-5006 can operate either 5GHz or 2.4GHz bands, offering the maximum speed of 1.3Gbps bandwidth it is also compatible with 802.11g/n that can work with 2.4GHz for longer range transmission.

MIMO technology with 3T3R and standard SMA / optional QMA type connectors

Lantech T(P)WMR-5006 series adapts MIMO technology with smart antenna transmission and reception for 3T3R. With six external detachable antenna SMA/QMA** connectors and optional antennas, T(P)WMR-5006 can have better Wi-Fi & LTE/GPS coverage.

Support AP/Bridge/Client mode, Mesh roaming

T(P)WMR-5006 supports AP/Bridge/Client mode for different applications.

It also supports client-base roaming to swap between the APs in a network.

Built-in Wireless Mesh network (WMN)

T(P)WMR-5006 supports Mesh network composed of different nodes. The set of SSIDs allow the wireless client to roam freely without the need for complicated account management. With Mesh protocol, it can provide a reliable, scalable, stable and seamless network topology.

Wireless WMM QoS

T(P)WMR-5006 supports 802.11e standard which defines a set of Quality of Service for wireless LAN applications as well as WMM (WIFI multimedia)

Advanced security & 16 SSIDs

The security support standards including 64/128bits WEP, WPA/WPA2 PSK (TKIP, AES), 802.1x ensures the best security and active defense against security trends. Lantech T(P)WMR-5006 support up to 16 SSIDs, each SSID has its independent security and encryption.

Load Balancing with 5 mechanism for multi-WANs

T(P)WMR-5006 supports Load Balancing for LTE / WAN connections. There are five schemes for Load Balancing function:

Pack	Algorithm	Description
Basic	Fixed	All traffic will be distributed to a single WAN.
	Failover	Routes connections through preferred WAN link while others stand-by. Sequentially activating another link if the preferred link fails.
	Priority	Select the active WAN according to priority.
	Weighted Round-Robin	Evenly distribute the traffic over all working WAN links in circular order according to the specified weights.
	Custom Route	Routing through the selected WAN for each specific traffic, ex: TCP/UDP port number and IP address.

2 port serial connection, Modbus gateway

It builds in 2 port serial connection for RS232; RS422; RS485 in which RS422/RS485 has 2.5KV isolation protection.

The built-in Modbus gateway can convert Modbus RTU/ASCII to Modbus TCP for device control.

VPN and firewall

Besides traditional VPN peer to peer tunneling, T(P)WMR-5006 support latest Multi-Site VPN function that is an efficient way for Mesh tunneling. The registration is under cloud service and encrypted by SSH makes the connection easy and safe.

It supports Multi-Site VPN, OpenVPN, L2TP over IPsec, IPsec, L2 over GRE, IPGRE, and NAT for various VPN applications.

The built-in Layer-4 firewall includes DDoS, IP address filter / Mac address filter / TCP / UDP port number.

Support Routing Protocol: Static route / RIPv2 / OSPF / BGP / EIGRP

Lantech router series supports two routing methods: static routing and dynamic routing. Dynamic routing makes use of RIPv2, OSPF, EIGRP and BGP. The user can either choose one routing method to establish the routing table.

Optional 2 GT smart bypass protection

The optional bypass relay is set to bypass the router to the next one when power is off in order to protect the network from crashing. Lantech bypass caters to remain in bypass mode until the router is completely booting up when power is back to avoid another network lost. Also it will be activated when detecting the router is hanged or link down.

DIDO for alarm & email notice; Event log; Remote Web control

2 sets of DIDO function can support additional high/low physical contact for designate applications besides Port / Power events, for example, DIDO function can trigger alarm if the router was moved or stolen. In case of events, the T(P)WMR-5006 will immediately send email and trap.

The event log can be sent via syslog, emails or trigger the alarm relay.

When the router is at remote area with limited access, Web control can help to get router status or remotely reboot by Web.

Wide range dual input voltage from dual input voltage from 16.8-137.5V (WV model)

The T(P)WMR-5006 is able to work from dual 16.8V ~137.5V DC input (WV model) and PoE model built-in PoE at/af with PoE budget 60W that is particular good for vehicle, rail train, depot etc applications.

Environmental monitoring for inside router info& alerting; Graphic WIFI & LTE signal strength

The built-in environmental monitoring can detect router ambient temperature, voltage, current and total PoE load where can send the syslog and email when abnormal.

The graphic WIFI & LTE signal strength shows connection status at a glance

Built-in Managed Switch Function

Managed switch function is built-in and provides various L2+ functions for network access deployment. It delivers ports and PoE management, VLAN, QoS, multicast, redundant ring, and security functions.

Dual image firmware

It supports dual-image firmware to choose which one to start.

Editable login page of captive portal

The T(P)WMR-5006 supports editable captive portal function that allows administrator to force end-users redirect to authentication page.


USB port for back up, restore configuration and upgrade firmware

The built-in USB port can upload/download/upgrade the firmware through USB dongle for router replacement

Ruggedized EN50155 design and FCC/CE & E-marking certificate**

The T(P)WMR-5006 series is verified with EN50155, EN61373, EN45545 standard with IP65/54 housing. It passed serious tests under extensive Industrial EMI and environmental vibration and shocks standards. With CE & FCC radio certification for LTE and E-marking** certificate, the T(P)WMR-5006 is best for outdoor community, vehicle, power substation, process control automation etc. For more usage flexibilities, T(P)WMR-5006 supports operating temperature from -40°C to 65°C.

DIMENSIONS (unit=mm)



SPECIFICATION

WLAN Interface	
Radio Frequency Type	DSSS, OFDM
Wireless Standard	IEEE 802.11ac/n/a 5GHz IEEE 802.11b/g/n 2.4GHz
Wireless bandwidth	5GHz: Up to 1300Mbps 2.4GHz: Up to 450Mbps
Modulation	802.11b: DSSS 802.11a/g: OFDM (BPSK, QPSK, 16-QAM, 64-QAM) 802.11n: OFDM (BPSK, QPSK, 16-QAM, 64-QAM) 802.11ac: OFDM (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM)
Operating Frequency	IEEE 802.11 a/b/g/n ISM Band, 2.412GHz~2.472GHz, 5150MHz~5850MHz
Transmission Rate	IEEE802.11ac: up to 1300Mbps IEEE802.11b: 1 / 2 / 5.5 / 11 Mbps IEEE802.11a/g: 6 / 9 / 12 / 18 / 24 / 36 / 48 / 54 Mbps IEEE802.11n: up to 450Mbps
IEEE 802.11b/g/n(2.4GHz)	Output Power Tx +/- 2dB(per chain) 18dBm @ 1~11Mbps 18dBm @ 6~54Mbps 20/20dBm @ MCS0~MCS7 (HT20/40) Receiver Sensitivity Rx +/- 2dB ≤ -95dBm @ 1~11Mbps ≤ -92dBm @ 6~18Mbps ≤ -88dBm @ 24Mbps ≤ -85dBm @ 36Mbps ≤ -81dBm @ 48Mbps ≤ -80dBm @ 54Mbps ≤ -94dBm @ MCS0 (HT20/40) ≤ -76dBm @ MCS7 (HT20/40)
IEEE 802.11a/n/ac(5GHz)	Output Power Tx +/- 2dB(per chain) 20dBm @ 6~24Mbps 16dBm @ 36~54Mbps 19/18dBm @ MCS0 (HT20/40) 16/16dBm @ MCS7 (HT20/40) 19/18/18dBm @ MCS0 (VHT20/40/80)
Encryption Security	13/13/13dBm @ MCS8 (VHT20/40/80) 13/13dBm @ MCS9 (VHT40/80) Receiver Sensitivity Rx +/- 2dB ≤ -92dBm @ 6~18Mbps ≤ -86dBm @ 24Mbps ≤ -84dBm @ 36Mbps ≤ -81dBm @ 48Mbps ≤ -80dBm @ 54Mbps ≤ -93dBm @ MCS0 (HT20/40) ≤ -71dBm/ ≤ -80dBm @ MCS7 (HT20/40) ≤ -90dBm @ MCS0 (VHT20/40/80) ≤ -69dBm @ MCS8 (VHT20/40/80) ≤ -66dBm @ MCS9 (VHT40/80)
Wireless Security	WEP : (64-bit , 128-bit key supported) WPA/WPA2 : IEEE802.11i(WEP and AES encryption) WPA-PSK (256-bit key pre-shared key supported) EAP-TLS,EAP-TTLS, and PEAP
Wireless Security	SSID broadcast disable
Cellular Interface	
Location Solutions	GPS, Glonass
Band Options	Europe & North America (EUNA model) LTE = B1, B2*, B3, B4*, B5*, B7, B8, B12*, B13*, B20, B25*, B26*, B29*, B30*, B41* (TDD) DC-HSPA+/ HSPA+/ HSPA/ UMTS = B1, B2*, B3*, B4*, B5*, B8
Data Rates – LTE	Europe & North America (EUNA model) Downlink (Cat 6): FDD: 300 Mbps TDD: 222 Mbps Uplink (Cat 6): FDD: 50 Mbps TDD: 26 Mbps
Software	
IPv6/4	Present
Operation Mode	AP/Bridge/Client/MESH mode
Login Security	Supports IEEE802.1x Authentication/RADIUS
Access Security	HTTP/HTTPS/Telnet/SSH & Administration; SNMP v1/v2/v3 access for authentication via MD5/SHA(v3) and Encryption via DES/AES(v3)
Protocol	PPPoE Client, DHCP server/client, Adjustable MTU,

	Port forwarding (NAPT), DMZ, NAT, SNTP, Firewall(Firewall(DDoS; IP address filter / Mac address filter / TCP/UDP port number),VRRP**, DDNS*
Routing	Static route / RIPv2 / OSPF / BGP / EIGRP
Management	SNMP v1, v2c, v3 / Web/Telnet/CLI
Load Balancing	5 schemes for multiple WAN
Basic	
Fixed	All traffic will be distributed to a single WAN.
Failover	Routes connections through preferred WAN link while others stand-by. Sequentially activating another link if the preferred link fails.
Priority	Select the active WAN according to priority.
Weighted Round-Robin	Evenly distribute the traffic over all working WAN links in circular order according to the specified weights
Custom Route	Routing through the selected WAN for each specific traffic ex: TCP/UDP port number and IP address.
Roaming	Client-base roaming
MESH	Support 802.11s Wireless Mesh Network
WMM	Wi-Fi multimedia and 802.11e traffic prioritization
Security	WEP64/128bits/ WPA/ WPA-PSK (TKIP,AES)/ WPA2/ WPA2-PSK (TKIP,AES)/SSH/SSL/HTTPS
Authentication	Radius Authentication, EAP-TLS, EAP-TTLS, PEAP; SSID broadcast disable supported
SSID	16 sets
Timer	Built-in Real Time Clock to keep track of time always(RTC)
Discovery	IEEE 802.1ab Link Layer Discovery Protocol (LLDP)
SNMP trap	Device cold / warm start Port link up / link down DI / DO high / low
Environmental Monitoring	System status for input voltage, current , ambient temperature to be shown in GUI and sent alerting if any abnormal status
Graphic signal display	Graphic LTE & Wi-Fi signal strength
Remote Web control	To reboot or get status of router by Web
Captive portal	Editable captive portal login page
Maintenance	Firmware upgradeable through TFTP/FTP/HTTP
Configuration backup & restore	Supports text configuration file for quick system installation USB port to upload/download firmware by USB dongle Dual image firmware
Physical Ports & System	
Connectors	10/100/1000T: 6x ports M12 8-pole X-coded (PoE model incl 4 PoE ports) USB/Console connector: 1 x M12 8-pole A-coded DI/DO : 1 x M12 5-pole A-coded Power Input connector : 1 x M12 4-pole A-coded Serial connector : 2 x M12 8-pole X-coded SIM card slots : 2 SMA/QMA** connector for LTE: 2 (female) SMA/QMA** connector for GPS: 1 (female) RP-SMA/QMA** connector for Wi-Fi: 3 (female)
Serial Baud Rate	1000Kbps high data rate,250kbps normal for RS232 ; 20Mbps high data rate,250kbps normal for RS422/RS485
Serial Data Bits	5, 6, 7, 8
Serial Parity	odd, even, none, mark, space
Serial Stop Bits	1, 1.5, 2
RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	Tx+, Tx-, Rx+, Rx-,GND
RS-485 (2-wire)	Data+, Data-,GND

Isolation protection	RS422/RS485 2.5KV isolation; 8KV contact & 15KV air RS232 8KV contact and 15KV air ESD DIDO 2.5KV isolation Input power 1.5KVA isolation
DI/DO	2 Digital Input (DI) : Level 0: -30~2V / Level 1: 10~30V Max. input current:8mA 2 Digital Output(DO): Open collector to 80 VDC, 50mA
EMMC Storage**	8/16/32 GB
LED Indicators	
Power & System indicator	Per unit: Power 1 (Green), Power 2 (Green), P-Fail (Red) , Ring Master(Green), System Ready(Green), Serial1/Serial2(Green) ,
10/100/1000Base-T(X) port indicator	Link/Activity (Green), Speed (Yellow) , PoE (Green, PoE model)
SIM	Green for Link/Act
GPS	Green for Link/Act
Fault	Red: Ethernet link down or power down
Fault contact	
Relay	Relay output to carry capacity of 1A at 24VDC
Power	
Input power	Dual DC input, 16.8VDC~137.5VDC for (WV model)
System power	30.5W
PoE Budget (PoE model)	60W
Physical Characteristic	
Enclosure	IP 65/54 aluminum case
Dimension	178 (W) x 99 (D) x 103 (H) mm
Weight	1450g
Environmental	
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Operating Temperature	-40°C ~ 65°C (-40°F ~ 149°F)
Operating Humidity	5% to 95% Non-condensing
Regulatory approvals	
EMC	FCC Part 15 Class A, EN55032 , EN55024
EMS	EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS), EN61000-4-8, EN61000-6-2
Radio Frequency	EN 301 489-1, EN 301 489-17, EN 301 489-19, EN 301 489-52, EN 300 440, EN 301 893, EN 300 328, EN 301 908-1※, EN 303 413, EN 62311
Safety	EN60950 (LVD), AS60950 (LVD)
Verifications & Report	EN50155, EN50121-3-2, EN50121-4 verification EN45545-2 R13/R22/R23/R24/R25 (EN ISO 4589-2, EN ISO 5659-2, NF X70-100-1 & 2) Fire & Smoke verification
Stability Testing	EN61373 (Shock & Vibration)
MTBF	495,724 Hrs (IEC62380 standards)
Warranty	5 years

*Future Release

**Optional

※Standard test of the following bands are not listed in EN 301 908-1 report (EUNA not listed bands) LTE = B2, B4, B5, B12, B13, B25, B26, B29, B30, B41
WCDMA = B2, B3, B4, B5;

RF Performance Table

	Data Rate	TX Power (per chain)	TX Power (3 chains)	Tolerance	RX Specifications Sensitivity	Tolerance
2.4GHz 802.11b	1Mbps	20dBm	25dBm	±2dB	-95dBm	±2dB
	2Mbps	20dBm	25dBm	±2dB	-94dBm	±2dB
	5.5Mbps	20dBm	25dBm	±2dB	-92dBm	±2dB
	11Mbps	20dBm	25dBm	±2dB	-90dBm	±2dB
2.4GHz 802.11g	6Mbps	21dBm	26dBm	±2dB	-94dBm	±2dB
	9Mbps	21dBm	26dBm	±2dB	-93dBm	±2dB
	12Mbps	21dBm	26dBm	±2dB	-93dBm	±2dB
	18Mbps	21dBm	26dBm	±2dB	-90dBm	±2dB
	24Mbps	21dBm	26dBm	±2dB	-90dBm	±2dB
	36Mbps	20dBm	25dBm	±2dB	-85dBm	±2dB
	48Mbps	19dBm	24dBm	±2dB	-82dBm	±2dB
	54Mbps	18dBm	23dBm	±2dB	-80dBm	±2dB
2.4GHz 802.11n HT20	MCS 0	21dBm	26dBm	±2dB	-94dBm	±2dB
	MCS 1	21dBm	26dBm	±2dB	-92dBm	±2dB
	MCS 2	21dBm	26dBm	±2dB	-89dBm	±2dB
	MCS 3	20dBm	25dBm	±2dB	-84dBm	±2dB
	MCS 4	20dBm	25dBm	±2dB	-83dBm	±2dB
	MCS 5	20dBm	25dBm	±2dB	-80dBm	±2dB
	MCS 6	18dBm	23dBm	±2dB	-79dBm	±2dB
	MCS 7	16dBm	21dBm	±2dB	-77dBm	±2dB
2.4GHz 802.11n HT40	MCS 0	20dBm	25dBm	±2dB	-93dBm	±2dB
	MCS 1	20dBm	25dBm	±2dB	-91dBm	±2dB
	MCS 2	20dBm	25dBm	±2dB	-89dBm	±2dB
	MCS 3	19dBm	24dBm	±2dB	-84dBm	±2dB
	MCS 4	19dBm	24dBm	±2dB	-82dBm	±2dB
	MCS 5	19dBm	24dBm	±2dB	-80dBm	±2dB
	MCS 6	18dBm	23dBm	±2dB	-79dBm	±2dB
	MCS 7	16dBm	21dBm	±2dB	-75dBm	±2dB

	Data Rate	TX Power (per chain)	TX Power (3 chains)	Tolerance	RX Specifications Sensitivity	Tolerance
5GHz 802.11a	6Mbps	20dBm	25dBm	±2dB	-94dBm	±2dB
	9Mbps	20dBm	25dBm	±2dB	-94dBm	±2dB
	12Mbps	20dBm	25dBm	±2dB	-92dBm	±2dB
	18Mbps	20dBm	25dBm	±2dB	-91dBm	±2dB
	24Mbps	20dBm	25dBm	±2dB	-90dBm	±2dB
	36Mbps	18dBm	23dBm	±2dB	-86dBm	±2dB
	48Mbps	16dBm	21dBm	±2dB	-83dBm	±2dB
	54Mbps	15dBm	20dBm	±2dB	-80dBm	±2dB
5GHz 802.11n/ac VHT20	MCS 0	19dBm	24dBm	±2dB	-93dBm	±2dB
	MCS 1	19dBm	24dBm	±2dB	-90dBm	±2dB
	MCS 2	19dBm	24dBm	±2dB	-87dBm	±2dB
	MCS 3	18dBm	23dBm	±2dB	-83dBm	±2dB
	MCS 4	18dBm	23dBm	±2dB	-80dBm	±2dB
	MCS 5	17dBm	22dBm	±2dB	-77dBm	±2dB
	MCS 6	16dBm	21dBm	±2dB	-74dBm	±2dB
	MCS 7	14dBm	19dBm	±2dB	-73dBm	±2dB
	MCS 8	13dBm	18dBm	±2dB	-71dBm	±2dB
5GHz 802.11n/ac VHT40	MCS 0	18dBm	23dBm	±2dB	-90dBm	±2dB
	MCS 1	18dBm	23dBm	±2dB	-88dBm	±2dB
	MCS 2	18dBm	23dBm	±2dB	-85dBm	±2dB
	MCS 3	17dBm	22dBm	±2dB	-82dBm	±2dB
	MCS 4	17dBm	22dBm	±2dB	-80dBm	±2dB
	MCS 5	16dBm	21dBm	±2dB	-75dBm	±2dB
	MCS 6	15dBm	20dBm	±2dB	-73dBm	±2dB
	MCS 7	14dBm	19dBm	±2dB	-73dBm	±2dB
	MCS 8	13dBm	18dBm	±2dB	-70dBm	±2dB
	MCS 9	13dBm	18dBm	±2dB	-68dBm	±2dB
5GHz 802.11ac VHT80	MCS 0	18dBm	23dBm	±2dB	-89dBm	±2dB
	MCS 1	18dBm	23dBm	±2dB	-87dBm	±2dB
	MCS 2	18dBm	23dBm	±2dB	-85dBm	±2dB
	MCS 3	17dBm	22dBm	±2dB	-83dBm	±2dB
	MCS 4	17dBm	22dBm	±2dB	-80dBm	±2dB
	MCS 5	16dBm	21dBm	±2dB	-78dBm	±2dB
	MCS 6	15dBm	20dBm	±2dB	-75dBm	±2dB
	MCS 7	14dBm	19dBm	±2dB	-72dBm	±2dB
	MCS 8	13dBm	18dBm	±2dB	-70dBm	±2dB
	MCS 9	13dBm	18dBm	±2dB	-68dBm	±2dB

ORDERING INFORMATION

All standard models are non-conformal coating, optional conformal coating are with -C model name; Optional bypass models are available with -BT model name; QMA connector models are with -Q model name.

- **TPWMR-5006-1L-1AC-2S-WV-65-EUNA.....P/N: 8653-021**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial ports + 6 Gigabit X-coded Ethernet managed Switch incl.4 PoE at/af with Load Balancing, VPN, Protocol Gateway; EU and US band; dual 16.8~137.5VDC input; IP65; -40~65C
- **TPWMR-5006-1L-1AC-2SA-WV-65-EUNA.....P/N: 8653-0211**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS422 ports + 6 Gigabit X-coded Ethernet managed Switch incl.4 PoE at/af with Load Balancing, VPN, Protocol Gateway; EU and US band; dual 16.8~137.5VDC input; IP65; -40~65C
- **TPWMR-5006-1L-1AC-2SB-WV-65-EUNA.....P/N: 8653-0212**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS485 ports + 6 Gigabit X-coded Ethernet managed Switch incl.4 PoE at/af with Load Balancing, VPN, Protocol Gateway; EU and US band; dual 16.8~137.5VDC input; IP65; -40~65C
- **TPWMR-5006-1L-1AC-2S-WV-54-EUNA.....P/N: 8653-041**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS232 ports + 6 Gigabit X-coded Ethernet managed Switch incl.4 PoE at/af with Load Balancing, VPN, Protocol Gateway; EU and US band; dual 16.8~137.5VDC input; IP54; -40~65C
- **TPWMR-5006-1L-1AC-2SA-WV-54-EUNA.....P/N: 8653-0411**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS422 ports + 6 Gigabit X-coded

- Ethernet managed Switch incl.4 PoE at/af with Load Balancing, VPN, Protocol Gateway; EU and US band; dual 16.8~137.5VDC input; IP54; -40~65C
- **TPWMR-5006-1L-1AC-2SB-WV-54-EUNA.....P/N: 8653-0412**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS485 ports + 6 Gigabit X-coded Ethernet managed Switch incl.4 PoE at/af with Load Balancing, VPN, Protocol Gateway; EU and US band; dual 16.8~137.5VDC input; IP54; -40~65C
 - **TWMR-5006-1L-1AC-2S-WV-65-EUNA.....P/N: 8650-021**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing, VPN, Protocol Gateway; EU and US band; dual 16.8V~137.5VDC input; IP65; -40~65C
 - **TWMR-5006-1L-1AC-2SA-WV-65-EUNA.....P/N: 8650-0211**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS422 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing, VPN, Protocol Gateway; EU and US band ; dual 16.8V~137.5VDC input; IP65 ; -40~65C
 - **TWMR-5006-1L-1AC-2SB-WV-65-EUNA.....P/N: 8650-0212**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing, VPN, Protocol Gateway; EU and US band ; dual 16.8V~137.5VDC input; IP65 ; -40~65C
 - **TWMR-5006-1L-1AC-2S-WV-54-EUNA.....P/N: 8650-041**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS232 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing, VPN, Protocol Gateway; EU and US band; dual 16.8V~137.5VDC input; IP54; -40~65C
 - **TWMR-5006-1L-1AC-2SA-WV-54-EUNA.....P/N:8650-0411**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS422 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing , VPN, Protocol Gateway; EU and US band ; dual 16.8V~137.5VDC input; IP54 ; -40~65C
 - **TWMR-5006-1L-1AC-2SB-WV-54-EUNA.....P/N:8650-0412**
EN50155 Multifunction VPN Router w/1x Wi-Fi 11ac + 1 LTE 4G SMA connectors + 2 serial RS485 ports + 6 Gigabit X-coded Ethernet managed switch for Load Balancing, VPN, Protocol Gateway; EU and US band ; dual 16.8V~137.5VDC input; IP54 ; -40~65C

EMMC Flash Storage

- **8G.....P/N:8850-113**
- **16G.....P/N:8850-114**
- **32G.....P/N:8850-115**

OPTIONAL ACCESSORIES

Management System

- **InstaAir.....P/N: 9000-121**
Cloud Based Fleet Management System for Routers

GPS Antenna

- **ANT12000001** SMA GPS antenna, 28dB, 300m



Cellular Antenna

- **ANT11000041** 2G/3G/4G dipole antenna, 791-960/1710~2170/2500~2700MHz, 3dBi, SMA plug, EU



- **ANT11000042** 2G/3G/4G dipole antenna, 704-960/1710~2170MHz, 3dBi, SMA plug, US



■ ANT11000046

LTE hinge rotatable antenna, 698-960MHz, 1710-2690MHz, Diameter 10mm, Length 108mm, SMA Connector



Wi-Fi Antenna

■ ANT11000051

2.4/5GHz SMA dipole Wi-Fi antenna, 3dBi (2.4GHz), 4dBi (5GHz)



■ ANT11000056

Wi-Fi hinge rotatable antenna, WiFi Dual Bands 2.4/5.8GHz, SMA Connector



Antenna Base

■ ADA11000052

Magnetic antenna base for Wi-Fi, RP SMA Jack Base, Length : 1M



■ ADA11000053

Magnetic antenna base for 3G/4G, RP SMA Jack Base, Length : 1M



Lantech Communications Global Inc.

www.lantechcom.tw
info@lantechcom.tw

© 2025 Copyright Lantech Communications Global Inc. all rights reserved. Updated on 16 APR 2026
The revise authority rights of product specifications belong to Lantech Communications Global Inc.
In a continuing effort to improve and advance technology, product specifications are subject to change without notice.