

I(P)ES-0008C

8 FE (PoE) at/af Industrial Ethernet Unmanaged Switch; 24V/48V input models



OVERVIEW

The Lantech I(P)ES-0008C is a compact Ethernet switch featuring a PoE budget of up to 240W (PoE model) and dual power input options ranging from 9-36V or 12-56VDC. It is designed for Ethernet switch systems in rail, metro, vehicle, or hardened industrial applications with a 24V input.

IES-0008C model: Dual 12/24/48V input and IPES-0008C: Dual 48V, 24V input with max PoE budget

The IES-0008C-24V accepts dual power input 9~36VDC while the IES-0008C accepts dual power input 12~56VDC. The POE model, IPES-0008C, supports the IEEE 802.3at/af standards, which can provide high power budget of up to 30W at each PoE port for PD devices like IP cameras and wireless access points etc. It accepts a power input of 9~36VDC, compliant with the IEEE 802.3at/af standards, and delivers up to 30W per PoE port, with a maximum output of 80W at 24V and 240W at 48V (with dual input). The PoE 48V model accepts power input of 45~56VDC and can provide a 48V output for PoE feeding in vehicles, with a maximum output of 240W at 48V input.


Ignition off mode with PoE off timer (IPES-0008C-IGN model) and sleep mode

The IPES-0008C supports an optional PoE feeding OFF timer dip switch (1/5/10 minutes or other intervals) when the vehicle's main key is turned off to prevent battery drain. IES-0008C Ignition model with a 60-minute countdown of standby mode to continue network operation and then into sleep mode to avoid the switch rebooting when ignition is back.

E-marking certificate, ISO 7637-2 compliant High reliability with Ethernet isolation and polarity reversal protection design and extended working temperature

The switch is designed with dual power inputs and is capable of withstanding EMI/RFI interference in the onboard or industrial harden network. The redundant power input design integrates inrush current protection also protects against polarity reversal. Additionally, the galvanic isolation feature shields the system from power transients often present in onboard and outdoor networks. It also meets the requirements of ISO 16750-2 P5A, reducing the impact of high-frequency pulse voltage that could be incurred by motor applications. The -E model can be used in extreme environments with an operating temperature range of -40°C to 75°C. The E-marking* certificate makes it the most suitable for bus, carriage, other vehicle applications.

DIMENSIONS (unit=mm)



*Note: The DIP switch in red color only appears on IGN models with PoE off timer.

SPECIFICATION

Hardware Specification		Negative (VCC-): RJ-45 pin 3,6
Standards	IEEE802.3 10Base-T Ethernet IEEE802.3u 100Base-TX IEEE802.3x Flow Control and Back Pressure IEEE802.3at/af Power over Ethernet	Power Consumption
Switch Architecture	Back-plane (Switching Fabric): 1.6Gbps	Galvanic Isolation
Transfer Rate	14,880pps for Ethernet port 148,800pps for Fast Ethernet port	Between power input and case ground Between the Ethernet port and case ground Between power input and Ethernet port
Mac Address	2K MAC address table	Case Dimension
Connectors	10/100TX: 8 x ports RJ-45 with Auto MDI/MDI-X function Power & P-Fail connector: 1 x 6-pole terminal block	Weight
Network Cable	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m)	Installation
LED	Per unit: Power 1 (Green), Power 2 (Green); Ethernet port: Link/Activity (Green) PoE: Active (Green)	EMI & EMS
Operating Humidity	5% ~ 95% (Non-condensing)	FCC Part 15 Subpart B, EN 55035:2017/A11:2020, EN 55032:2015/A11:2020, IEC 61000-4-2:2008, IEC 61000-4-3:2020, IEC 61000-4-4:2012, IEC 61000-4-5:2014+AMD1:2017 CSV, IEC 61000-4-6:2023, IEC 61000-4-8:2009, IEC 61000-6-2:2016, IEC 61000-6-4:2018, EN IEC 61000-6-2:2019, EN IEC 61000-6-4:2019, BS EN 55035:2017/A11:2020, BS EN 55032:2015/A11:2020,
Operating Temperature	-20°C~60°C / -4°F~140°F (Standard model) -40°C~75°C / -40°F~167°F(-E model)	Safety
Storage Temperature	-40°C~85°C / -40°F~185°F	EN 62368 (LVD)
Power Supply	9~36VDC (24V model); 45~56VDC (48V model) 12~56VDC (non-PoE model)	Stability Testing
PoE Budget (PoE model)	240W for 45~56V input (48V model) (50~57VDC input is recommended for 802.3at 30W applications) 80W at 24V input A higher PoE budget can be applied upon request. **	IEC 60068-2-27 (Shock), IEC 60068-2-31 (Shock), IEC 60068-2-64 (Vibration), IEC 60068-2-80 (Vibration)
PoE pin assignment (PoE model)	RJ-45 port # 1~#8 supports IEEE 802.3at/af End-point, Alternative A mode. Per port provides up to 30W Positive (VCC+): RJ-45 pin 1,2	Vehicle certificate
		E24 marking (24V model)
		MTBF
		965,429 hrs (IEC62830 standards)

*Future Release
**Optional

ORDERING INFORMATION

- **IPES-0008C-48V.....P/N: 8351-149**
8 10/100TX w/8 PoE Mode A 802.3at/af 30W Industrial Ethernet Switch; dual 45~56VDC input; -20°C to 60°C
- **IPES-0008C-48V-E.....P/N: 8351-14901**
8 10/100TX w/8 PoE Mode A 802.3at/af 30W Industrial Ethernet Switch; dual 45~56VDC input; -40°C to 75°C
- **IPES-0008C-24V.....P/N: 8351-1491**
8 10/100TX w/8 PoE Mode A 802.3at/af 30W Industrial Ethernet Switch, dual 9V~36VDC input; compliant with ISO7637; -20°C to 60°C
- **IPES-0008C-24V-E.....P/N: 8351-14911**
8 10/100TX w/8 PoE Mode A 802.3at/af 30W Industrial Ethernet Switch, dual 9V~36VDC input, compliant with ISO7637; -40°C to 75°C
- **IPES-0008C-24V-IGN.....P/N: 8351-1492**
8 10/100TX w/8 PoE Mode A 802.3at/af 30W Industrial Ethernet Switch, dual 9V~36VDC input; compliant with ISO7637; -20°C to 60°C w/ignition
- **IPES-0008C-24V-IGN-E.....P/N: 8351-14921**
8 10/100TX w/8 PoE Mode A 802.3at/af 30W Industrial Ethernet Switch, dual 9V~36VDC input, compliant with ISO7637; -40°C to 75°C w/ignition
- **IES-0008C-48V.....P/N: 8351-1493**
8 10/100TX Industrial Ethernet Switch, dual 12V~56VDC input; compliant with ISO7637-2; -20°C to 60°C w/Ethernet galvanic isolation
- **IES-0008C-48V-E.....P/N: 8351-14931**
8 10/100TX Industrial Ethernet Switch, dual 12V~56VDC input, compliant with ISO7637-2; -40°C to 75°C w/Ethernet galvanic isolation
- **IES-0008C-24V.....P/N: 8351-1494**
8 10/100TX Industrial Ethernet Switch, dual 9V~36VDC input; compliant with ISO7637-2; -20°C to 60°C w/Ethernet galvanic isolation
- **IES-0008C-24V-E.....P/N: 8351-14941**
8 10/100TX Industrial Ethernet Switch, dual 9V~36VDC input, compliant with ISO7637-2; -40°C to 75°C w/Ethernet galvanic isolation
- **IES-0008C-24V-IGN.....P/N: 8351-1495**
8 10/100TX Industrial Ethernet Switch, dual 9V~36VDC input; compliant with ISO7637-2; -20°C to 60°C w/Ethernet galvanic isolation & ignition
- **IES-0008C-24V-IGN-E.....P/N: 8351-14951**
8 10/100TX Industrial Ethernet Switch, dual 9V~36VDC input, compliant with ISO7637-2; -40°C to 75°C w/Ethernet galvanic isolation & ignition

OPTIONAL ACCESSORIES

DIN Rail Power

- **NDR-480 Series** 480W Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)
- **NDR-240 Series** 240W Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)
- **NDR-120 Series** 120W Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C; For 115VAC, please refer to derating curve on NDR-120 Series datasheet)
- **NDR-75 Series** 75W Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C; For 115VAC, please refer to derating curve on NDR-120 Series datasheet)

Lantech Communications Global Inc.

www.lantechcom.tw
info@lantechcom.tw

© 2025 Copyright Lantech Communications Global Inc. all rights reserved. Updated on 18 MAR 2026
 The revise authority rights of product specifications belong to Lantech Communications Global Inc.
 In a continuing effort to improve and advance technology, product specifications are subject to change without notice.