

# PRODUCT LEAFLET

## UPS COMPOSITE WRAPPING

**UPS COMPOSITE WRAPPING** pipe repair solutions are suitable for sealing leaks in pipes with diameters ranging from as small as 1/2 inch (1.2 cm) to as large as 48 inches (121 cm). Once these products have fully cured, they can withstand pressures of up to 300 psi and temperatures of up to 150°C/302°F.



## COMPOSITE PIPE REPAIR

<b>UPS 19000 RH THISTLEBOND STANDARD RESIN &amp; HARDENER</b>	Epoxy gel applied with a brush, designed for use in combination with Resimac technical fabrics to wrap and effectively seal large-diameter pipes.
<b>UPS 19003 THISTLEBOND A&amp;B CEMENT</b>	An epoxy paste of trowelable consistency intended for the repair of severely corroded or pitted pipe surfaces.

## FEATURES & BENEFITS

<b>Solvent free</b>	Fix leaking pipes in under an hour.
<b>Epoxy &amp; Polyurethane resin technology</b>	Applicable to GRP/Glass Fiber, plastic, concrete, or metal surfaces.
<b>Fast curing grade</b>	Prolong the lifespan of troublesome pipes.
<b>GRP, Glass Fibre wrap for larger diameter pipes</b>	Eliminate the necessity for hot work or welding.
<b>Surface tolerant</b>	Decreased Health & Safety hazards.

## APPLICATIONS

<b>Diesel</b>	Low Concentration Chemicals
<b>Sea Water</b>	Drinking Water
<b>Steam</b>	Effluent

