

UPS 510 UN UNI-NOX – WATER BASED ACRYLIC MEMBRANE TOPCOAT – UV



Is a single component water based acrylic topcoat. The coating can be applied to manually, mechanically, hydro-blasted, and abrasive cleaned surfaces to provide long term corrosion protection.

- Water based acrylic technology
- Single component
- Apply by brush, roller, or standard airless spray
- Flexible with excellent elongation
- Touch dry in 30 minutes at 20°C
- Tolerant of less-than-ideal surface preparation
- No primer required on metallic surfaces
- UV stable
- Provides long term protection in C1 – C5 corrosive environments

FOOD & BEVERAGE STORAGE TANK



PETROL STORAGE TANK



CRUDE OIL STORAGE TANK



Product Applications

UPS 510 UN UNI-NOX is typically used within:

- **Bridges**
 - **Stairways**
 - **External tank surfaces**
 - **Structural steel**
 - **Containers**
 - **Transformers**
 - **Pylons**
-

Global Availability

UPS 510 UN UNI-NOX is available from a network of Global Distributors for prompt delivery. For further details and the location of your local distributor, please contact Unique Polymer Systems on:

+44(0) 1531 636300 | sales@uniquepolymersystems.com

Technical Service

Complete technical assistance is available. Please contact Unique Polymer Systems with your requirements:

+44(0) 1531 636300 | sales@uniquepolymersystems.com
