



C1500

Fully-automated water management system for commercial applications

The Chemigem C1500 is a fully-automated water management system suitable for commercial applications of all sizes. Health regulations in many Australian States require water chemistry to be automated and the Chemigem C1500 provides a reliable, cost-effective solution for public aquatic facilities.

C1500 Commercial chlorine and pH controller supplied complete with pair of C1500 peristaltic pump and commercial injection manifold with NRV.

Chemicals are precisely dosed via either highly-efficient commercial-sized C1500 peristaltic dosing pumps. You can purchase a Chemigem C1500 Complete, which includes a pair of C1500 dosing pumps and a commercial injection valve or the components of the Chemigem C1500 can be purchased separately.

Pool Controls is proud to offer a twelve month warranty on C1500 units and spare parts used in commercial and semi-commercial applications. Please contact Pool Controls for full commercial warranty terms.

Call +61 (8) 9240 4400
sales@poolcontrols.com.au | service@poolcontrols.com.au
poolcontrols.com.au

Balance
Experience
Innovation



C1500

The Australian-made Chemigem C1500 is a tried-and-tested water management system for commercial and semi-commercial applications.

It is a fully-automated dosing system that complies with the new NSW Health Regulations and other applicable legislation. It represents real value for money, and in Australia, is backed up by a national team of dedicated Service Technicians, who are happy to assist with installation, technical issues and ongoing maintenance.

Product	Dose Rate	Total Dose at 50% Duty
C1500 C1500 Peripumps	1500mL/min	750mL/min overall 30 second feed each



C1500 Peristaltic Pump Specifications

The highly-efficient C1500 peristaltic pump is able to deliver up to 1500mL per minute, ensuring full sanitisation for large pools and bather loads.

Specifications may alter at anytime without notice

Enclosure	Plastic case, Wall Mounting (Rear keyhole slots).		
Power Supply	240 Volt 50 Hz. Others on request	Nominal Current	0.5 amps
Pumps	240V AC Peristaltic		
Motors Speed	100 rpm	Flow Rates	1500 mL / min
Squeeze Tube	EPDM, Maximum continuous working pressure of 100 kPa		
Maximum Nominal	1500 ml/min (1 cps), adjustable by time		

Call +61 (8) 9240 4400

sales@poolcontrols.com.au | service@poolcontrols.com.au

poolcontrols.com.au

Balance
Experience
Innovation



**POOL
CONTROLS**