

# THINK SAFE!

Here at Fish Window Cleaning® safety is our top priority. We follow OSHA guidelines to ensure our cleaners and our customers stay safe at all times.

Must keep conductive objects at least 10 feet away from unguarded & exposed lines.

\*OSHA 1926.1408

Powerlines must be deenergized or insulated before work can be completed.

\*OSHA 1926.1408



When work is being done 15ft or less from an edge, one of the following safety systems must be in place; guardrail, safety net, or personal fall protection.

\*OSHA 1910.28



[www.fishwindowcleaning.com/](http://www.fishwindowcleaning.com/)

# THINK SAFE!

Here at Fish Window Cleaning® safety is our top priority. We follow OSHA guidelines to ensure our cleaners and our customers stay safe at all times.

Must keep conductive objects at least 10 feet away from unguarded & exposed lines.

\*OSHA 1926.1408

Powerlines must be deenergized or insulated before work can be completed.

\*OSHA 1926.1408



When work is being done 15ft or less from an edge, one of the following safety systems must be in place; guardrail, safety net, or personal fall protection.

\*OSHA 1910.28



[www.fishwindowcleaning.com/](http://www.fishwindowcleaning.com/)



[www.fishwindowcleaning.com/](http://www.fishwindowcleaning.com/)

# THINK SAFE!

Here at Fish Window Cleaning® safety is our top priority. We follow OSHA guidelines to ensure our cleaners and our customers stay safe at all times.

Must keep conductive objects at least 10 feet away from unguarded & exposed lines.

\*OSHA 1926.1408

Powerlines must be deenergized or insulated before work can be completed.

\*OSHA 1926.1408



When work is being done 15ft or less from an edge, one of the following safety systems must be in place; guardrail, safety net, or personal fall protection.

\*OSHA 1910.28



[www.fishwindowcleaning.com/](http://www.fishwindowcleaning.com/)