



WE BELIEVE IN **PRECISION**. WE BELIEVE IN **RELIABILITY**. WE BELIEVE IN **RESULTS**.

Pressure Sensitive Film Applicator Laminator

Specifications: 12", 36", 48", 60" models

Machine dimension includes tables:

12" unit – 30" wide x 43" deep x 28" height

36" unit – 52" wide x 43" deep x 28 "height

48" unit – 72" wide x 43" deep x 28 "height

60" unit – 84" wide x 45" deep x 30 "height

Standard Features:

Designed for graphics and rigid substrate applications

Rigid steel frame, two rubber coated rolls, air operated nip

pressure, foot switch control for hands free operation. Unwind

shaft with 3" core.

Maximum sign size:

12" unit – 12" wide x 2" thick

30" unit – 32" wide x 2" thick

48" unit – 50" wide x 2" thick

60" unit – 62" wide x 2" thick

Net machine weight:

12" unit – 150 lbs

30" unit – 220 lbs

48" unit – 250 lbs

60" unit – 320 lbs

Applicator speed:

Variable speed with reverse

From 0 – 80 feet per minute.

Unwind OD of 9.5" inch

Options:

- 5' loading roller conveyor with dual edge guides.
- 5' unloading roller conveyor.
- Machine stand
- Micrometer stops on air cylinders.
- Powered Rewind for release liner with 3" core.

Increased web speeds available.

Conveyors available with legs for a stand alone unit.

CONTACT US