



SOLID
TO SUCCEED

灵云 SMART CLOUD


MOBILE ELEVATING WORK PLATFORM

14 m Series

XG1412HA



The print does not belong to the contract, nor a part of the vehicle purchase contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product.



Parameter

Item	Unit	XG1412HA
Dimension		
Max. working height	m	13.8
Max. platform height	m	11.8
Overall length a	mm	2477
Overall length (without ladder)	mm	2267
Overall width b	mm	1190
Overall height c	mm	2610
Overall height (platform folded)	mm	2060
Platform dimension (length d * Width e)	mm	2280 × 1120
Extended platform dimension	mm	900
Min. ground clearance (elevated/stowed state)	mm	20 / 100
Tire	mm	381 × 127
Wheelbase f	mm	1877
Performance		
Max. number of occupants	/	2
Work platform rated load	kg	320
Extension platform rated load	kg	115
Travel speed (lowered/elevated position)	km/h	3.2 / 0.8
Min. turning radius (inside/outside wheel)	m	0 / 2.3
Work platform raising/lowering time	s	45-70 / 52-78
Max. gradeability	%	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3
Total weight	kg	2920
Power source		
Battery	/	Maintenance free lead-acid battery
Battery capacity	AH	200-225Ah

