



**SOLID**  
TO SUCCEED

灵云 SMART CLOUD


MOBILE ELEVATING WORK PLATFORM

**10** m Series

XG1008HA



The print does not belong to the contract, nor a part of the vehicle purchase contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product.


**Parameter**

Item	Unit	XG1008HA
<b>Dimension</b>		
Max. working height	m	10
Max. platform height	m	8
Overall length a	mm	2477
Overall length (without ladder)	mm	2280
Overall width b	mm	810
Overall height c	mm	2350
Overall height (platform folded)	mm	1985
Platform dimension (length d * Width e)	mm	2280 × 810
Extended platform dimension	mm	900
Min. ground clearance (elevated/stowed state)	mm	20 / 100
Tire	mm	381 × 127
Wheelbase f	mm	1877
<b>Performance</b>		
Max. number of occupants	/	2
Work platform rated load	kg	230
Extension platform rated load	kg	115
Travel speed (lowered/elevated position)	km/h	3.5 / 0.8
Min. turning radius (inside/outside wheel)	m	0 / 2.3
Work platform raising/lowering time	s	29-40 / 34-45
Max. gradeability	%	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3
Total weight	kg	2220
<b>Power source</b>		
Battery	/	Maintenance free lead-acid battery
Battery capacity	AH	170

