



SOLID
TO SUCCEED



MOBILE ELEVATING WORK PLATFORM

8
m
Series

XG0807HD XG0807HDW
XG0807HA XG0807HAW
XG0807AC XG0807ACW



The print does not belong to the contract, nor a part of the vehicle purchase contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product.

Parameter

Item	Unit	XG0807HD	XG0807HDW	XG0807HA	XG0807HAW	XG0807AC	XG0807ACW
Dimension							
Max. working height	m	7.8	7.8	7.8	7.8	7.8	7.8
Max. platform height	m	5.8	5.8	5.8	5.8	5.8	5.8
Overall length a	mm	1900	1900	1900	1900	1900	1900
Overall length (without ladder)	mm	1680	1680	1680	1680	1680	1680
Overall width b	mm	760	810	760	810	760	810
Overall height c	mm	2160	2160	2160	2160	2160	2160
Overall height (platform folded)	mm	1830	1830	1830	1830	1830	1830
Platform dimension (length d * Width e)	mm	1670 × 740	1670 × 740	1670 × 740	1670 × 740	1670 × 740	1670 × 740
Extended platform dimension	mm	900	900	900	900	900	900
Min. ground clearance (elevated/stowed state)	mm	20 / 71	20 / 71	20 / 71	20 / 71	20 / 71	20 / 71
Tire	mm	323 × 100	323 × 100	323 × 100	323 × 100	323 × 100	323 × 100
Wheelbase f	mm	1360	1360	1360	1360	1360	1360
Performance							
Max. number of occupants	/	2	2	2	2	2	2
Work platform rated load	kg	230	230	230	230	230	230
Extension platform rated load	kg	115	115	115	115	115	115
Travel speed (lowered/elevated position)	km/h	3 / 0.8	3 / 0.8	3 / 0.8	3 / 0.8	4.5 / 0.8	4.5 / 0.8
Min. turning radius (inside/outside wheel)	m	0 / 1.75	0 / 1.75	0 / 1.75	0 / 1.75	0 / 1.75	0 / 1.75
Work platform raising/lowering time	s	15-25 / 25-35	15-25 / 25-35	15-25 / 25-35	15-25 / 25-35	15-25 / 25-35	15-25 / 25-35
Max. gradeability	%	25	25	25	25	25	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3	1.5 / 3	1.5 / 3	1.5 / 3	1.5 / 3	1.5 / 3
Total weight	kg	1550	1580	1485	1580	1550	1580
Power source							
Battery	/	Maintenance free lead-acid battery					
Battery capacity	AH	170					
Options		AC power to the platform Air-line to platform Platform working light Weighing overload alarm					

