



SOLID  
TO SUCCEED

灵云 SMART  
CLOUD

MOBILE ELEVATING WORK PLATFORM

8<sup>m</sup>  
Li  
Series XG0807HA-li



The print does not belong to the contract, nor a part of the vehicle purchase contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product.



Parameter

Item	Unit	XG0807HA-li
<b>Dimension</b>		
Max. working height	m	7.8
Max. platform height	m	5.8
Overall length a	mm	1900
Overall width b	mm	760
Overall height c	mm	2160
Overall height (platform folded)	mm	1830
Extended platform dimension	mm	900
Min. ground clearance (elevated/stowed state)	mm	20 / 71
Tire	mm	323 × 100
<b>Performance</b>		
Max. number of occupants	/	2
Work platform rated load/extension platform load	kg	230/115
Travel speed (lowered/elevated position)	km/h	3 / 0.8
Min. turning radius (inside/outside wheel)	m	0 / 1.75
Work platform raising/lowering time	s	15-25 / 25-35
Max. gradeability	%	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3
Total weight	kg	1485
<b>Power source</b>		
Battery	/	Lithium battery
Battery capacity	AH	150

