



SOLID  
TO SUCCEED



MOBILE ELEVATING WORK PLATFORM

12<sup>m</sup>  
Li Series XG1212HA-li



The print does not belong to the contract, nor a part of the vehicle purchase contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product.

Parameter		
Item	Unit	XG1212HA-li
<b>Dimension</b>		
Max. working height	m	12
Max. platform height	m	10
Overall length a	mm	2480
Overall width b	mm	1190
Overall height c	mm	2480
Overall height (platform folded)	mm	1930
Extended platform dimension	mm	900
Min. ground clearance (elevated/stowed state)	mm	20 / 100
Tire	mm	381 × 127
<b>Performance</b>		
Max. number of occupants	/	2
Work platform rated load/extension platform load	kg	320/115
Travel speed (lowered/elevated position)	km/h	3.2 / 0.8
Min. turning radius (inside/outside wheel)	m	0 / 2.3
Work platform raising/lowering time	s	50-75 / 43-65
Max. gradeability	%	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3
Total weight	kg	3000
<b>Power source</b>		
Battery	/	Lithium battery
Battery capacity	AH	202

