



SOLID
TO SUCCEED



MOBILE ELEVATING WORK PLATFORM

10^m
Li Series XG1008HA-li



The print does not belong to the contract, nor a part of the vehicle purchase contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product.



Parameter

Item	Unit	XG1008HA-li
Dimension		
Max. working height	m	10
Max. platform height	m	8
Overall length a	mm	2480
Overall width b	mm	810
Overall height c	mm	2350
Overall height (platform folded)	mm	1999
Extended platform dimension	mm	900
Min. ground clearance (elevated/stowed state)	mm	20 / 100
Tire	mm	381 × 127
Performance		
Max. number of occupants	/	2
Work platform rated load/extension platform load	kg	230/115
Travel speed (lowered/elevated position)	km/h	3.5 / 0.8
Min. turning radius (inside/outside wheel)	m	0 / 2.3
Work platform raising/lowering time	s	29-40 / 34-45
Max. gradeability	%	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3
Total weight	kg	2220
Power source		
Battery	/	Lithium battery
Battery capacity	AH	172

