



**SOLID**  
TO SUCCEED



MOBILE ELEVATING WORK PLATFORM

**XG0608HA**



The print does not belong to the contract, nor a part of the vehicle purchase contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product.

**Parameter**

Item	Unit		XG0608HA
<b>Dimension</b>			
Max. working height	m		6.6
Max. platform height	m		4.6
Overall length a	mm		1568
Overall length (without ladder)	mm		1410
Overall width b	mm		810
Overall height c	mm		2076
Overall height (platform folded)	mm		1714
Platform dimension (length d * Width e)	mm		1372 × 702
Extended platform dimension	mm		600
Min. ground clearance (elevated/stowed state)	mm		33 / 61
Tire	mm		280 × 76
Wheelbase f	mm		1130
<b>Performance</b>			
Max. number of occupants	/		2
Work platform rated load	kg		200
Extension platform rated load	kg		115
Travel speed (lowered/elevated position)	km/h		3.0 / 0.5
Min. turning radius (inside/outside wheel)	m		0.45 / 1.6
Work platform raising/lowering time	s		22–33 / 22–33
Max. gradeability	%		25
Tilt alarm angle (sideways/forward or back)	°		1.5 / 3
Total weight	kg		870
<b>Power source</b>			
Battery	/		Maintenance free lead-acid battery
Battery capacity	AH		100
Options		AC power to the platform Air-line to platform Platform working light Weighing overload alarm	

